

## EPC2012C – Enhancement Mode Power Transistor

 $V_{DS}$ , 200 V $R_{DS(on)}$ , 100 mΩ $I_D$ , 5 A

Gallium Nitride's exceptionally high electron mobility and low temperature coefficient allows very low  $R_{DS(on)}$ , while its lateral device structure and majority carrier diode provide exceptionally low  $Q_G$  and zero  $Q_{RR}$ . The end result is a device that can handle tasks where very high switching frequency, and low on-time are beneficial as well as those where on-state losses dominate.

## Maximum Ratings

PARAMETER		VALUE	UNIT
$V_{DS}$	Drain-to-Source Voltage (Continuous)	200	V
$I_D$	Continuous ( $T_A = 25^\circ\text{C}$ , $R_{\theta JA} = 26^\circ\text{C/W}$ )	5	A
	Pulsed ( $25^\circ\text{C}$ , $T_{PULSE} = 300 \mu\text{s}$ )	22	
$V_{GS}$	Gate-to-Source Voltage	6	V
	Gate-to-Source Voltage	-4	
$T_J$	Operating Temperature	-40 to 150	$^\circ\text{C}$
$T_{STG}$	Storage Temperature	-40 to 150	

## Thermal Characteristics

PARAMETER		TYP	UNIT
$R_{\theta JC}$	Thermal Resistance, Junction-to-Case	4.2	$^\circ\text{C/W}$
$R_{\theta JB}$	Thermal Resistance, Junction-to-Board	12.5	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (Note 1)	85	

Note 1:  $R_{\theta JA}$  is determined with the device mounted on one square inch of copper pad, single layer 2 oz copper on FR4 board. See [https://epc-co.com/epc/documents/product-training/Appnote\\_Thermal\\_Performance\\_of\\_eGaN\\_FETs.pdf](https://epc-co.com/epc/documents/product-training/Appnote_Thermal_Performance_of_eGaN_FETs.pdf) for details.

Static Characteristics ( $T_J = 25^\circ\text{C}$  unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$BV_{DSS}$	Drain-to-Source Voltage	$V_{GS} = 0 \text{ V}$ , $I_D = 60 \mu\text{A}$	200			V
$I_{DSS}$	Drain-Source Leakage	$V_{GS} = 0 \text{ V}$ , $V_{DS} = 160 \text{ V}$		10	50	$\mu\text{A}$
$I_{GSS}$	Gate-to-Source Forward Leakage	$V_{GS} = 5 \text{ V}$		0.2	1	mA
	Gate-to-Source Reverse Leakage	$V_{GS} = -4 \text{ V}$		10	50	$\mu\text{A}$
$V_{GS(TH)}$	Gate Threshold Voltage	$V_{DS} = V_{GS}$ , $I_D = 1 \text{ mA}$	0.8	1.4	2.5	V
$R_{DS(on)}$	Drain-Source On Resistance	$V_{GS} = 5 \text{ V}$ , $I_D = 3 \text{ A}$		70	100	mΩ
$V_{SD}$	Source-Drain Forward Voltage	$I_S = 0.5 \text{ A}$ , $V_{GS} = 0 \text{ V}$		1.9		V

All measurements were done with substrate connected to source.



EPC2012C eGaN® FETs are supplied only in passivated die form with solder bars

## Applications

- High Frequency DC-DC Conversion
- Class D Audio
- Wireless Power Transfer

## Benefits

- Ultra High Efficiency
- Ultra Low  $R_{DS(on)}$
- Ultra Low  $Q_G$
- Ultra Small Footprint



Dynamic Characteristics ( $T_j = 25^\circ\text{C}$  unless otherwise stated)

PARAMETER		TEST CONDITIONS	MIN	TYP	MAX	UNIT
$C_{ISS}$	Input Capacitance	$V_{DS} = 100\text{ V}, V_{GS} = 0\text{ V}$		100	140	pF
$C_{RSS}$	Reverse Transfer Capacitance			0.4	0.6	
$C_{OSS}$	Output Capacitance			64	85	
$R_G$	Gate Resistance			0.6		$\Omega$
$Q_G$	Total Gate Charge	$V_{DS} = 100\text{ V}, V_{GS} = 5\text{ V}, I_D = 3\text{ A}$		1	1.3	nC
$Q_{GS}$	Gate-to-Source Charge	$V_{DS} = 100\text{ V}, I_D = 3\text{ A}$		0.3		
$Q_{GD}$	Gate-to-Drain Charge			0.2	0.35	
$Q_{G(TH)}$	Gate Charge at Threshold			0.2		
$Q_{OSS}$	Output Charge	$V_{DS} = 100\text{ V}, V_{GS} = 0\text{ V}$		10	13	
$Q_{RR}$	Source-Drain Recovery Charge			0		

All measurements were done with substrate connected to source.

Note 2:  $C_{OSS(ER)}$  is a fixed capacitance that gives the same stored energy as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 50%  $BV_{DSS}$ .

Note 3:  $C_{OSS(TR)}$  is a fixed capacitance that gives the same charging time as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 50%  $BV_{DSS}$ .

Figure 1: Typical Output Characteristics at 25°C




Figure 2: Transfer Characteristics




Figure 3:  $R_{DS(on)}$  vs.  $V_{GS}$  for Various Drain Currents




Figure 4:  $R_{DS(on)}$  vs.  $V_{GS}$  for Various Temperatures




Figure 5a: Capacitance (Linear Scale)




Figure 5b: Capacitance (Log Scale)




Figure 6: Gate Charge




Figure 7: Reverse Drain-Source Characteristics




Figure 8: Normalized On Resistance vs. Temperature





Figure 9: Normalized Threshold Voltage vs. Temperature



All measurements were done with substrate shorted to source.

Figure 10: Gate Current




Figure 11: Transient Thermal Response Curves







Figure 12: Safe Operating Area



**TAPE AND REEL CONFIGURATION**


4 mm pitch, 8 mm wide tape on 7" reel



Dimension (mm)	EPC2012C (note 1)		
	target	min	max
a	8.00	7.90	8.30
b	1.75	1.65	1.85
c (note 2)	3.50	3.45	3.55
d	4.00	3.90	4.10
e	4.00	3.90	4.10
f (note 2)	2.00	1.95	2.05
g	1.5	1.5	1.6

Note 1: MSL 1 (moisture sensitivity level 1) classified according to IPC/JEDEC industry standard.  
 Note 2: Pocket position is relative to the sprocket hole measured as true position of the pocket, not the pocket hole.


**DIE MARKINGS**




Part Number	Laser Markings		
	Part # Marking Line 1	Lot_Date Code Marking line 2	Lot_Date Code Marking Line 3
EPC2012C	2012	YYYY	ZZZZ

**DIE OUTLINE**

Solder Bar View



Side View



DIM	MICROMETERS		
	MIN	Nominal	MAX
A	1681	1711	1741
B	889	919	949
c	662	667	672
d	245	250	255
e	230	245	260
f	245	250	255
g	600	600	600

Pad no. 1 is Gate;

Pad no. 2 is Substrate;\*


Pad no. 3 is Drain;

Pad no. 4 is Source

\*Substrate pin should be connected to Source

**RECOMMENDED LAND PATTERN**

(units in  $\mu\text{m}$ )



The land pattern is solder mask defined.

Pad no. 1 is Gate;

Pad no. 2 is Substrate;\*


Pad no. 3 is Drain;

Pad no. 4 is Source

\*Substrate pin should be connected to Source

**RECOMMENDED STENCIL DRAWING**

(units in  $\mu\text{m}$ )



Recommended stencil should be 4 mil (100  $\mu\text{m}$ ) thick, must be laser cut, opening per drawing. The corner has a radius of R60.

Intended for use with SAC305 Type 3 solder, reference 88.5% metals content.

Additional assembly resources available at <https://www.epc-co.com/epc/DesignSupport/AssemblyBasics.aspx>

Efficient Power Conversion Corporation (EPC) reserves the right to make changes without further notice to any products herein to improve reliability, function or design. EPC does not assume any liability arising out of the application or use of any product or circuit described herein; neither does it convey any license under its patent rights, nor the rights of others. eGaN® is a registered trademark of Efficient Power Conversion Corporation. EPC Patent Listing: [epc-co.com/epc/AboutEPC/Patents.aspx](http://epc-co.com/epc/AboutEPC/Patents.aspx)

Information subject to change without notice. Revised April, 2021