

Data sheet | Item number: 249-138

Test plug module; without locking device; modular; for 4-conductor terminal blocks; gray

www.wago.com/249-138



Data
Electrical data

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Ratings per IEC/EN

Ratings (note)	Maximum test voltage (touch contact): 48 V (test pins are not touch-proof)
Nominal voltage (III/3)	500 V

Ratings per IEC/EN 2

Ratings (note) 2	Maximum test current (touch contact): 0.5 A Maximum test current: 6 A (if the test pins are securely connected in the clamping units)
------------------	------------------------------------------------------------------------------------------------------------------------------------------

General information

Test voltage	500 V
Test current	0.5 A

Physical data

Width	8 mm / 0.315 inches
Module width	8 mm / 0.315 inches

Material Data

Note (material data)	Information on material specifications can be found here
Color	gray
Insulation material	Polyamide (PA66)
Fire load	0.104 MJ
Weight	1.3 g

Commercial data

Product Group	2 (Terminal Block Accessories)
eCl@ss 10.0	27-14-11-48
eCl@ss 9.0	27-14-11-48
ETIM 8.0	EC002555
ETIM 7.0	EC002555
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE

Subject to changes. Please also observe the further product documentation!



GTIN	4045454359973
Customs tariff number	85366990990

Environmental Product Compliance

CAS-No.	7439-92-1
REACH Candidate List Substance	Lead
RoHS Compliance Status	Compliant,With Exemption
RoHS Exemption	6(c) 7(a) 7(c)-I 7(c)-II
SCIP notification number (Austria)	49b6921b-e745-4d6a-8ddb-6b3f340417a1
SCIP notification number (Belgium)	50c873aa-ce13-4e30-ab4e-9adb59d94ded
SCIP notification number (Bulgaria)	c516e619-ab32-4af6-940d-597525c3081d
SCIP notification number (Czech Republic)	0865b9d0-1564-4972-816f-d53032665ef1
SCIP notification number (Denmark)	7bc54153-d8e9-452c-9d7a-687d508ee438
SCIP notification number (Finland)	6be4f7a4-129f-484a-a4b0-103da2af6b83
SCIP notification number (France)	0bd316cb-03d1-4234-bcf8-45f5572ec581
SCIP notification number (Germany)	6f2ba8d9-c1e3-4349-afac-95220f391089
SCIP notification number (Hungary)	4af9e7b7-693d-402c-a686-b557b400b255
SCIP notification number (Italy)	17fe9b05-3091-4a41-8cdf-4ed7e1c170fe
SCIP notification number (Netherlands)	1bf7fd6f-5723-455d-824b-90caf37ff4aa
SCIP notification number (Poland)	3df95b8e-68af-4906-8d33-889a86169935
SCIP notification number (Romania)	9dbfa58c-c2e9-47aa-98d1-3fc3489cff4e
SCIP notification number (Sweden)	ade9cab-c-dde1-4c62-b145-15b12ab45ec9

Optional accessories

Testing and measuring

Testing accessories	
Item no.: 210-136	www.wago.com/210-136
Test plug; 2 mm Ø; with 500 mm cable; red	

Downloads

Documentation

Bid Text

249-138	2019 年2月19 日	xml	Download
X81 - Datei		3.2 kB	

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



249-138	2017 年8月18 日	doc 24.6 kB	Download
doc - Datei			

Additional Information

pdf 2.3 MB	Download
---------------	----------

CAD/CAE-Data

CAE data

WSCAD Universe 249-138	URL	Download
------------------------	-----	----------

CAD data

2D/3D Models 249-138	URL	Download
----------------------	-----	----------


Environmental Product Compliance

Compliance Search

Environmental Product Compliance 249-138	URL	Download
Test plug module; without locking device; modular; for 4-conductor terminal blocks; gray		

Installation Notes

Installation



Snapping individual modules together to assemble a multi-pole test plug module.

Testing

Subject to changes. Please also observe the further product documentation!



Testing via test plug modules snapped onto a terminal strip – wired or unwired. As touch contact is made with the CAGE CLAMP® (spring steel) unit, this testing type is limited to maximum 0.5 A.

Testing after the conductors have been terminated.

Distance between locking devices must be approximately 35 ... 40 mm!

Subject to changes. Please also observe the further product documentation!