



REV. A  
DCO 144521

COIL: @ 25°C	
RESISTANCE	880 OHMS ±10%
NOMINAL VOLTAGE	18.0 VDC
MUST OPERATE	10.5 VDC
MUST RELEASE	6.0 VDC MAX, 0.91 VDC MIN.
ENVIRONMENT:	
VIBRATION	10 Hz TO 3000 Hz @ 30 g's
SHOCK	100 g's 11 MS. DURATION
TEMPERATURE	-65 °C TO +125 °C
NOTES:	
OPERATE TIME 2 MS MAX	
RELEASE TIME 1.5 MS MAX	
OPERATE BOUNCE 1.0 MS MAX	
RELEASE BOUNCE 1.5 MS MAX	

CUSTOMER DATA SHEET	
<p>TERMINAL VIEW</p>	
CONTACT RATING: LOW LEVEL TO 1A	
28 VDC RESISTIVE 100,000 OPERATIONS	
DR. B.D. 11SEP2008	CK <i>[Signature]</i>
<p>©COPYRIGHT 2005 TYCO ELECTRONICS CORPORATION ALL INTERNATIONAL RIGHTS RESERVED</p>	

CUST. C. I. I. STD.	TE NUMBER 1617105-5
CUST. NO. _____ REV. _____	

CII PART NUMBER	MW 6HP-18P
-----------------	------------