

# FQ 2,54D/ 20-PV- 380-1-BT - Pin strip



1156915

<https://www.phoenixcontact.com/us/products/1156915>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



SMD pin header, nominal current: 3 A, Test voltage: 500 V AC, number of positions: 20, pitch: 2.54 mm, color: black, contact surface: Gold, contact connection type: Pin, mounting: SMD soldering

## Your advantages

- Reliable mechanical and electrical connections thanks to the double-sided contact system
- Designed for integration into the SMT soldering process
- Clear and cost-optimized design
- Suitable for a multitude of applications
- Stacked, coplanar or orthogonal PCB connections enable maximum flexibility in the device

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 1156915       |
| Packing unit                         | 1 pc          |
| Minimum order quantity               | 190 pc        |
| Sales key                            | AA24          |
| Product key                          | AAXGBB        |
| GTIN                                 | 4063151160623 |
| Weight per piece (including packing) | 2.27 g        |
| Weight per piece (excluding packing) | 2.27 g        |
| Customs tariff number                | 85366930      |
| Country of origin                    | CN            |

1156915

<https://www.phoenixcontact.com/us/products/1156915>

## Technical data

### Notes

|                    |  |
|--------------------|--|
| Notes on operation | The permissible voltage during operation depends on the application, taking into consideration the air clearances and creepage distances within the scope of insulation requirements in accordance with IEC 60664-1. |
|--------------------|--|


### Product properties

|                     |                     |
|---------------------|---------------------|
| Product type        | SMD pin header      |
| Product family      | FQ 2,54D/...-PV     |
| Number of positions | 20                  |
| Pitch               | 2.54 mm             |
| Number of rows      | 2                   |
| Pin layout          | Linear pad geometry |

### Electrical properties

|                       |   |
|-----------------------|---|
| Nominal current $I_N$ | 3 A IEC 60512-5-2:2002-02 (at 20°C 80-pos.) |
| Degree of pollution   | 3   |
| Contact resistance    | 20 mΩ                                       |
| Test voltage          | 500 V AC IEC 60512-4-1:2003                 |

### Dimensions

|                     |  |
|---------------------|--|
| Dimensional drawing |  |
| Pitch               | 2.54 mm  |
| Width [w]           | 25.4 mm  |
| Height [h]          | 10.2 mm  |
| Length [l]          | 7.6 mm   |
| Installed height    | 8.8 mm   |

### Application

|               |  |
|---------------|--|
| Contact cover | 0.4 mm   |
| Stack height  | 13.6 mm Tolerance: +1.3 mm (in combination with Range of articles:FQ 2,54D/...-SV) |
| Wipe length   | 1.3 mm   |

### PCB design

|              |               |
|--------------|---------------|
| Pad geometry | 1.02 x 3.4 mm |
|--------------|---------------|

## Material specifications

### Material data - contact

1156915

<https://www.phoenixcontact.com/us/products/1156915>

|   |  |
|---|--|
| Note                                      | WEEE/RoHS-compliant, free of whiskers according to IEC 60068-2-82/JEDEC JESD 201 |
| Contact material                          | Cu alloy   |
| Surface characteristics                   | Selective coating  |
| Metal surface contact area (top layer)    | Gold (Au)  |
| Metal surface contact area (middle layer) | Nickel (Ni)  |
| Metal surface soldering area (top layer)  | Tin (Sn)   |

## Material data - housing

|  |              |
|--|--------------|
| Color (Housing)                        | black (9005) |
| Insulating material                    | PA           |
| Insulating material group              | I            |
| CTI according to IEC 60112             | 600          |
| Flammability rating according to UL 94 | V0           |

## Connector

### Connection 1

|                            |     |
|----------------------------|-----|
| Insulating material        | PA  |
| CTI according to IEC 60112 | 600 |

## Electrical tests

### Thermal test | Test group C

|                            |                       |
|----------------------------|-----------------------|
| Specification              | IEC 60512-5-2:2002-02 |
| Tested number of positions | 80                    |

### Insulation resistance

|  |                       |
|--|-----------------------|
| Specification                                | IEC 60512-3-1:2002-02 |
| Insulation resistance, neighboring positions | > 1 GΩ                |

### Air clearances and creepage distances |

|   |        |
|---|--------|
| Insulating material group                         | I      |
| Minimum value for clearance and creepage distance | 0.4 mm |

## Mechanical tests

### Insertion and withdrawal forces

|                                     |             |
|-------------------------------------|-------------|
| Result                              | Test passed |
| No. of cycles                       | 100         |
| Insertion strength per pos. approx. | 2.9 N       |
| Withdraw strength per pos. approx.  | 2.9 N       |

### Visual inspection

|               |                       |
|---------------|-----------------------|
| Specification | IEC 60512-1-1:2002-02 |
| Result        | Test passed           |

### Dimension check

1156915

<https://www.phoenixcontact.com/us/products/1156915>

|               |                       |
|---------------|-----------------------|
| Specification | IEC 60512-1-2:2002-02 |
| Result        | Test passed           |

## Environmental and real-life conditions

### Vibration test

|                        |                       |
|------------------------|-----------------------|
| Specification          | IEC 60068-2-6:2007-12 |
| Frequency              | 10 - 55 - 10 Hz       |
| Sweep speed            | 1 octave/min          |
| Amplitude              | 1.52 mm               |
| Sweep speed            | 181 m/s <sup>2</sup>  |
| Test duration per axis | 2 h                   |

### Durability test

|  |                                   |
|--|-----------------------------------|
| Specification                                | IEC 60512-9-1:2010-03 (following) |
| Contact resistance R <sub>1</sub>            | 20 mΩ                             |
| Contact resistance R <sub>2</sub>            | 30 mΩ                             |
| Insertion/withdrawal cycles                  | 100                               |
| Insulation resistance, neighboring positions | > 1 GΩ                            |

### Ambient conditions

|   |                   |
|---|-------------------|
| Ambient temperature (operation)         | -40 °C ... 125 °C |
| Ambient temperature (storage/transport) | -40 °C ... 70 °C  |
| Relative humidity (storage/transport)   | 30 % ... 70 %     |
| Ambient temperature (assembly)          | -5 °C ... 100 °C  |

## Mounting

|               |                     |
|---------------|---------------------|
| Mounting type | SMD soldering       |
| Pin layout    | Linear pad geometry |

### Processing notes

|   |                  |
|---|------------------|
| Process                                   | Reflow soldering |
| Moisture Sensitive Level                  | MSL 1            |
| Classification temperature T <sub>c</sub> | 260 °C           |

# FQ 2,54D/ 20-PV- 380-1-BT - Pin strip




1156915

<https://www.phoenixcontact.com/us/products/1156915>

## Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1156915>

|  <b>cULus Recognized</b><br>Approval ID: E118976 |                       |                       |                   |                             |
|---|-----------------------|-----------------------|-------------------|-----------------------------|
|   | Nominal voltage $U_N$ | Nominal current $I_N$ | Cross section AWG | Cross section $\text{mm}^2$ |
|   | 30 V                  | 3 A                   | -                 | -                           |

1156915

<https://www.phoenixcontact.com/us/products/1156915>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27460201 |
| ECLASS-13.0 | 27460201 |
| ECLASS-12.0 | 27460201 |

### ETIM

|          |          |
|----------|----------|
| ETIM 8.0 | EC002637 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# FQ 2,54D/ 20-PV- 380-1-BT - Pin strip



1156915

<https://www.phoenixcontact.com/us/products/1156915>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)