

Specification Sheet

Part Number: TAG76T1-795



Metalized polyester has a matte finish, allowing for the highest resolution and print contrast. The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Thermal Transfer Labels, 2.5" x 2.0", 1 Across, Polyester, Silver, 1000/roll

Article Number	596-76795
Type	TAG76T1
Color	Silver (SR)
Quantity Per	roll
Product Description	HellermannTyton’s metalized polyester labels include a layer of metallic particles that give the appearance of being made of metal. Applications include asset tracking and product rating plates. The high operating temperature makes them suitable for use on electronic equipment. Great for replacing expensive metal stampings, engravings and even silk screened rating plates, the printed labels offer high quality imaging for text and graphics and can be permanently placed on a wide variety of flat surfaces.
Short Description	Thermal Transfer Labels, 2.5" x 2.0", 1 Across, Polyester, Silver, 1000/roll

Global Part Name	TAG76T1-795-SR
------------------	----------------

Width W (Imperial)	2.50
--------------------	------

Width W (Metric)	63.5
------------------	------

Bundle Diameter Min (Imperial)	0.14
--------------------------------	------

Bundle Diameter Min (Metric)	3.50
------------------------------	------

Bundle Diameter Max (Imperial)	0.30
--------------------------------	------

Bundle Diameter Max (Metric)	7.62
------------------------------	------

Thickness T (Metric)	64.0
----------------------	------

Height H (Imperial)	2.0
---------------------	-----

Height H (Metric)	50.8
-------------------	------

Width of Liner (Metric)	66.5
-------------------------	------

Width of Liner (Imperial)	2.62
---------------------------	------

Material	Type 795, Polyester (795)
----------	---------------------------

Material Shortcut	795
-------------------	-----

Adhesive	Acrylic
----------	---------

Halogen Free	No
UV Resistant (Yes/No)	No
Adhesive Operating Temperature	-40°F to +300°F (-40°C to +149°C)
Operating Temperature	-40°F to +300°F (-40°C to +149°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL-Recognized
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919102055
Labels per Column	1
Labels per Row	1

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)