



Technical Data Sheet

USB 3.2 G1 4-Port Industrial USB Hub with Power Supply with GL 3520 Chipset 7~48V Input

Model Number: USBG-3X4Mr2

Rev 01.200716



The USBG-3X4MR2 is an USB3 Hub that comply with the Universal Serial Bus (USB) Specifications Revision 3.2 G1 and work up to 5Gbps.

Features

- USB 3.2 Gen 1 compliant
- Charges all 4 USB Ports up to 1.5A Each Simultaneously
- Provides 4 LEDs Indicating Data Transferring for each Port
- Supports 15KV ESD Surge Protection for Each Port
- Multi Transaction Translators (Multi-TT)

Product Information

- Model Number: USBG-3X4Mr2
- Packing List:
 - Hub, Power Supply, Screw Lock USB Cable, User Manual

Specifications

OVERVIEW

Product Type	USB Hub
USB Specification	USB 3.2 Gen 1
Maximum Data Rate	5Gb/sec
Electrical Protections	N/A
Mountable	Surface Mount
Material	Steel
Compliance	CE, FCC, RoHS, TAA

CONNECTIONS

Downstream Port Count	4
Downstream Port Type	4x Type A USB 3.2 G1 / 3.0
Power Input	7 ~ 48V DC

ENVIRONMENTAL

Operating Temperature	0C ~ 55C
Operating Humidity	5% to 95% RH
Storage Temperature	-20C ~ 75C

DIMENSIONS

Length	7.05 inches
Width	2.33 inches
Height	0.91 inches

OS SUPPORT

Supported Operating Systems	OS independent; No software or drivers required
-----------------------------	---

WARRANTY

Warranty Period	1 Year
-----------------	--------

PRODUCT URL

USBG-3X4Mr2 Product Page	https://www.coolgear.com/product/usb-3-0-4-port-industrial-usb-hub-with-power-supply-with-gl-3520-chipset-748v-input
--------------------------	---

© 2020 Coolgear, Inc. All Rights Reserved. All products and accompanying digital documentation including images are the property and / or trademarks of Coolgear Inc. Coolgear Inc. are continuously improving upon its products. Product specifications are subject to change without notice