NSYTBP885

PC box IP66 IK08 RAL7035 Int.H80W80D65 Ext.H89W89D51 opaque PC cover H10





Thalassa
Thalassa TBP
Multi-purpose
Industrial box
3.50 in (89 mm)
3.50 in (89 mm)
2.13 in (54 mm)
3.15 in (80 mm)
3.15 in (80 mm)
1.85 in (47 mm)
Wall mounted
1 body
1 cover
4 cover screw
Set of 5
One piece moulded
Low plain cover
Metal screws
Captive screw flat outside sealed area

Cover by captive screws

Complementary

Material	polycarbonate	
Color	Gray RAL 7035)	
Standards	UL 508 A IEC 62208	
Product Certifications	TÜV UL	
Electrical Insulation Class	Class II	
Mounting location	Outdoor	
Net Weight	0.24 lb(US) (0.108 kg)	

Removable parts

Environment

IP degree of protection	IP66 conforming to NEMA 4.4X
IK degree of protection	IK08 IEC 62262
Fire resistance	1760 °F (960 °C)
Ambient Air Temperature for Storage	5140 °F (-1560 °C)
Operating temperature	-13176 °F (-2580 °C)

Ordering and shipping details

Category	80033-ENCLOSURE SYSTEMS POLYESTER	
Discount Schedule	ES1	
GTIN	3606480165597	
Nbr. of units in pkg.	1	
Package weight(Lbs)	3.81 oz (108.0 g)	
Returnability	No	
Country of origin	HU	

Packing Units

- <u></u>	
Unit Type of Package 1	PCE
Package 1 Height	2.01 in (5.1 cm)
Package 1 width	3.50 in (8.9 cm)
Package 1 Length	3.50 in (8.9 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	160
Package 2 Weight	41.14 lb(US) (18.66 kg)
Package 2 Height	16.14 in (41.0 cm)
Package 2 width	23.62 in (60.0 cm)
Package 2 Length	62.99 in (160.0 cm)
Unit Type of Package 3	PAL
Number of Units in Package 3	4000
Package 3 Weight	1061.53 lb(US) (481.5 kg)
Package 3 Height	39.37 in (100.0 cm)
Package 3 width	47.24 in (120.0 cm)
Package 3 Length	1574.80 in (4000.0 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	[®] REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	[™] Product Environmental Profile
Circularity Profile	[®] End Of Life Information

Contractual warranty

Warranty 1	8 months
------------	----------