WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board **Engineering Specification**

1. **Product Number**





2. **Features**

- *Stable and reliable in performances
- *Low profile, compact size
- *RoHS compliance
- *SMT processes compatible

3. **Applications**

- *ISM 2.4 GHz applications
- *ZigBee/BLE applications
- *Bluetooth earphone systems
- *Hand-held devices when WiFi / Bluetooth functions are needed, e.g., Smart phones
- *IEEE802.11 b/g/n
- *Wireless PCMCIA cards or USB dongles

4. **Description**

Unictron's AA055A ceramic chip antenna is designed for ISM 2.4GHz applications, covering frequencies 2400~2500MHz. Fabricated with proprietary designand processes, AA055A shows excellent performance and is fully compatible with SMT processes which can decrease the assembly cost and improve device's quality and consistency.



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT **PERMISSION**

Prepared by: Xenia Designed by: Phillip Checked by : Mike Approved by : Herbert

TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board Engineering Specification

DOCUMENT NO.

H2B1BG2A1B0100


REV. A

5. Layout Guide & Electrical Specifications


5-1. Layout Guide (unit: mm)

Solder Land Pattern:

The solder land pattern (gold marking areas) is shown below. Recommendation on matching circuit will be provided according to customer's installation conditions.



Transmission Line with 50Ω Impedance Characteristic



Bottom View

Unictron
T echnologies Corp.

2016-10-18

Document



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Xenia Designed by : Phillip Checked by : Mike Approved by : Herbert

TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board Engineering Specification

DOCUMENT NO.

H2B1BG2A1B0100

5-2. Electrical Specifications (Evaluation Board Dimensions: 80 x 40 mm²) 5-2-1. Electrical Table

Characte	ristics	Specifications	Unit
Outline Dimensions		3.2 x 1.6 x 0.5	mm
Ground Plane Dime	nsions	80 x 40	mm
Working Frequency		2400~2500	MHz
VSWR (@ center fre	equency)*	2 Max.	
Characteristic Imped	dance	50	Ω
Polarization		Linear Polarization	
Peak Gain	(@2442 MHz)	2.5 (typical)	dBi
Efficiency	(@2442 MHz)	84 (typical)	%

^{*}Center frequency means the frequency with the lowest value in return loss of the chip antenna on the evaluation board.

Unictron
T echnologies Corp.

2016-10-18

Document



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Xenia Designed by : Phillip Checked by : Mike Approved by : Herbert


TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board Engineering Specification

DOCUMENT NO.

H2B1BG2A1B0100



6. Outline Dimensions of Antenna & Evaluation Board (unit: mm) 6-1. Antenna Dimensions



NOTE:

1.All materials are RoHS compliant.
2. Arc Compliant.
3. Compliant.
3. Reference Dimensions.

PIN Definitions





PIN	1	2 Unictron
Soldering PAD	Signal	Tuning / Ground 2016-10-18

Document



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com


THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Xenia Designed by : Phillip Checked by : Mike Approved by : Herbert

TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board Engineering Specification


DOCUMENT NO.


H2B1BG2A1B0100





7. Radiation Pattern (with 80 x 40 mm² Evaluation Board)

7-1. 3D Gain Pattern @ 2442 MHz (unit: dBi)









Unictron
Technologies Corp.

詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Xenia Designed by : Phillip Checked by : Mike Approved by : Herbert


TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board Engineering Specification

DOCUMENT NO.

H2B1BG2A1B0100

7-2. 3D Efficiency Table																
Frequency(MHz)	2400	2412	2417	2422	2427	2432	2437	2442	2447	2452	2457	2462	2467	2472	2484	2500
Efficiency(dB)	-1.4	-1.0	-0.9	-0.8	-0.8	-0.8	-0.7	-0.7	-0.8	-0.8	-0.8	-0.9	-0.9	-1.0	-1.2	-1.4
Efficiency(%)	72.8	78.7	80.4	82.3	83.0	83.9	84.4	84.5	84.1	84.0	83.2	82.0	80.5	78.6	75.4	72.5
Peak Gain(dBi)	1.5	1.8	1.9	2.1	2.3	2.3	2.4	2.5	2.5	2.5	2.4	2.4	2.2	2.1	1.9	1.8

7-3. 3D Efficiency vs. Frequency



Unictron
T echnologies Corp.

2016-10-18

Document



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Xenia Designed by : Phillip Checked by : Mike Approved by : Herbert


TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board Engineering Specification

DOCUMENT NO.

H2B1BG2A1B0100


8. Frequency tuning and Matching circuit

8-1. Chip antenna tuning scenario:



8-2. Matching circuit:

With the following recommended values of matching and tuning components, the center frequencies will be about 2442 MHz at our standard 80x40 mm² evaluation board. However, these are typical reference values which may need to be changed when circuit boards or part vendors are different.



System Matching Circuit Component							
Location	Description	Vendor	Tolerance				
1	1.2pF, (0402)	DARFON	±0.1 pF				
2	3.3nH, (0402)	DARFON	±0.1 nH				
3	N/A	- /	nictron_				
4 Fine tuning element	1.2pF, (0402)	DARFO <u>2016</u>	- 1±9.18F				



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION


Prepared by : Xenia Designed by : Phillip Checked by : Mike Approved by : Herbert


TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board Engineering Specification

DOCUMENT NO.

H2B1BG2A1B0100

8-3. Reference for frequency tuning element







詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by : Xenia Designed by : Phillip Checked by : Mike Approved by : Herbert

TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board Engineering Specification

DOCUMENT NO.

H2B1BG2A1B0100

9. Reminders for users of Unictron's AA055A ceramic chip antennas

- 9-1. This chip antenna is made of ceramic materials which are relatively more rigid and brittle compared to printed circuit board materials. Bending of circuit board at the locations where chip antenna is mounted may cause the cracking of solder joints or antenna itself.
- 9-2. Punching/cutting of the break-off tab of PCB panel may cause severe bending of the circuit board which may result in cracking of solder joints or chip antenna itself. Therefore break-off tab shall be located away from the installation site of chip antenna.
- 9-3. Be cautious when ultrasonic welding process needs to be used near the locations where chip antennas are installed. Strong ultrasonic vibration may cause the cracking of chip antenna solder joints.

10. Operating & Storage Conditions

10-1. Operating

(1) Maximum Input Power: 2 W

(2) Operating Temperature: -40°C to 85°C

10-2. Storage

(1) Storage Temperature: -5° C to 40° C

(2) Relative Humidity: 20% to 70%

(3) Shelf Life: 1 year

11. Notice

All specifications are subject to change without notice.

Unictron
T echnologies Corp.

2016-10-18

Document



詠業科技股份有限公司

Unictron Technologies Corporation Website:www.unictron.com

THIS DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF UNICTRON TECHNOLOGIES CORPORATION AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS OR DEVICES WITHOUT PERMISSION

Prepared by: Xenia Designed by: Phillip Checked by: Mike Approved by: Herbert

TITLE: WiFi/Bluetooth Ceramic Chip Antenna (AA055A) with Evaluation Board Engineering Specification

DOCUMENT NO.

H2B1BG2A1B0100