



RSC13-5-3-A

Ruland RSC13-5-3-A, 0.313" x 0.188" Short Slit Coupling, Aluminum, Clamp Style, 0.787" OD, 0.846" length



Description

Ruland RSC13-5-3-A is a clamp style slit coupling with 0.3125" x 0.1875" bores, 0.787" OD, and 0.846" length. It is manufactured from a single piece of material and has two sets of intermittent slit cuts allowing for a maintenance-free coupling with high torsional stiffness in relation to comparable couplings, such as beam type. RSC13-5-3-A is commonly used in precise positioning applications found in semiconductor, medical, and test and measurement equipment. This short style slit coupling is ideal for compact installations where the long type may not fit. It is a suitable alternative to comparatively sized disc couplings due to the ability to accommodate all forms of misalignment whereas a single disc coupling has no accommodation for parallel misalignment. RSC13-5-3-A is zero-backlash, has a balanced design for reduced vibration at speeds up to 7,500 RPM, and can accommodate all forms of misalignment with light bearing loads. It is manufactured by Reliance Precision Ltd. in their County Cork, Ireland factory from 7075 aluminum for lightweight and low inertia. RSC13-5-3-A is inventoried by Ruland and RoHS3 and REACH compliant.

Product Specifications

Bore (B1)	0.3125 in	Small Bore (B2)	0.1875 in
B1 Max Shaft Penetration	0.339 in	B2 Max Shaft Penetration	0.339 in
Outer Diameter (OD)	0.787 in	Bore Tolerance	+0.001 in / -0.000 in
Length (L)	0.846 in	Clearance Diameter (C) MAX	0.858 in
Cap Screw	M2.5	Screw Material	18-8 300 Series Stainless Steel
Hex Wrench Size	2.0 mm	Screw Finish	Bright
Seating Torque	0.73 Nm	Number of Screws	2
Dynamic Torque Reversing	8.4 lb-in	Angular Misalignment	3°
Dynamic Torque Non-Reversing	12.8 lb-in	Parallel Misalignment	0.005 in
Peak Torque	21.7 in-lb	Axial Motion	0.020 in
Torsional Stiffness	16.8 lb-in/Deg	Moment of Inertia	0.0026893 lb-in ²
Maximum Speed	7,500 RPM	Full Bearing Support Required?	Yes
Zero-Backlash?	Yes	Balanced Design	Yes
Material Specification	7075-T651 Extruded and Drawn Aluminum Bar	Temperature	-110°F to 175°F (-80°C to 80°C)
Finish Specification	SurTec 650	Manufacturer	Reliance Precision Limited
Country of Origin	Ireland	Weight (lbs)	0.030600
UPC	634529299906	Tariff Code	8483.60.8000
UNSPC	31163003		
Note 1	Performance ratings are for guidance only. The user must determine suitability for a particular application.		

Prop 65

⚠ WARNING This product can expose you to the chemical Nickel (metallic), known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.