



Inch table

Dimensions in: inches - millimeters

1 d ₁	2 d ₂ Thread		3 Length l ±0.06	d ₃	h ₁	h ₂ min.	t
1.38 35.1	1/4 x 20	-	.50 12.7	.69 17.5	.86 21.8	.41 10.4	-
1.38 35.1	1/4 x 20	5/16 x 18	1.00 25.4	.69 17.5	.86 21.8	.41 10.4	.50 12.7
1.75 44.5	5/16 x 18	3/8 x 16	.75 19.1	1.06 26.9	1.22 31.0	.66 16.8	.50 12.7
2.38 60.5	5/16 x 18	-	-	.75 19.1	1.34 34.0	.63 16.0	.50 12.7
2.38 60.5	3/8 x 16	-	-	.75 19.1	1.34 34.0	.56 14.2	.50 12.7
2.38 60.5	1/2 x 13*	-	-	1.25 31.8	1.34 34.0	.56 14.2	.56 14.2

*This size has a zinc plated steel tapped insert

Specification

- Fluted star knob
Polypropylene plastic
- Temperature resistant up to 150 °F (66 °C)
- Black, textured finish
- Tapped Insert
- Brass, molded-in
- Steel, zinc plated (thread d₂=1/2x13)
- Threaded stud
Steel
- Zinc plated
- Molded-in
- RoHS compliant

Information

FKBH and FKZS fluted star knobs are an economical choice for light duty clamping or securing applications.

see also...

- Fluted Star Knobs FKTH (with Tapped Through Insert)

On request

- Additional thread sizes

How to order (With brass tapped insert) FKBH-1.75-5/16X18	1 Handle diameter d ₁
	2 Thread d ₂
How to order (With steel threaded stud) FKZS-1.38-1/4X20-0.50	1 Handle diameter d ₁
	2 Thread d ₂
	3 Length l