

## Housing - HC-STA-B16-CHWS-1TTP21-ELC-AL - 1412647

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling housings B16, With single locking latch, Material: Die-cast aluminum, salt water resistant, Cable outlets: 1, straight, Height: 79 mm, Cable gland: none, Gland: no, 1x Pg21, Standard

### Why buy this product

- good shielding in the event of electromagnetic interference



### Key Commercial Data

|                      |          |
|----------------------|----------|
| Packing unit         | 1 STK    |
| Custom tariff number | 85389099 |
| Country of origin    | China    |

### Technical data

#### Dimensions

|        |         |
|--------|---------|
| Height | 79 mm   |
| Width  | 44 mm   |
| Length | 93.5 mm |

#### Ambient conditions

|  |   |
|--|---|
| Degree of protection of housing (IP)   | IP66  |
|  | IP69K (ISO 20653:2013-02, with suitable screw connection) |
|  | IP67  |
| Degree of protection of housing (NEMA) | 4   |
|  | 4X  |
|  | 12  |
| Ambient temperature (operation)        | -40 °C ... 125 °C   |

# Housing - HC-STA-B16-CHWS-1TTP21-ELC-AL - 1412647


## Technical data

### General

|                              |   |
|------------------------------|---|
| Note                         | For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K |
| Size                         | B16   |
| Housing type                 | Coupling housings   |
| Locking type                 | With single locking latch                                   |
| No. of cable outlets         | 1   |
| Cable exit                   | straight  |
| Screw connection             | none  |
| Type of the screw connection | 1x Pg21   |
| Housing material             | Die-cast aluminum, salt water resistant                     |
| Housing surface material     | Uncoated  |
| Seal material                | NBR, conductive   |
| Material lock                | PA  |

## Drawings

Dimensional drawing



Dimensional drawing

## Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27143424 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 8.0 | 27440202 |
| eCl@ss 9.0 | 27440202 |

ETIM

|          |          |
|----------|----------|
| ETIM 5.0 | EC000437 |
|----------|----------|

# Housing - HC-STA-B16-CHWS-1TTP21-ELC-AL - 1412647

## Approvals

Approvals

---

Approvals

EAC / GL

---

Ex Approvals

---

Approvals submitted

---

## Approval details

|     |
|-----|
| EAC |
|-----|

|    |
|----|
| GL |
|----|

## Accessories

### Accessories

#### Full screw connection

Cable gland - G-INS-PG21-M68N-NNES-S - 1411175



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 13 mm ... 18 mm, Shielding: No, Connecting thread: Pg21, Color: silver

---

Cable gland - G-INSEC-PG21-M68N-NNES-S - 1411200



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 13 mm ... 18 mm, Shielding: yes, Connecting thread: Pg21, Color: silver

---

## Housing latches

## Housing - HC-STA-B16-CHWS-1TTP21-ELC-AL - 1412647

### Accessories

Replacement part - HC-STA-B10-SL-PLBK - 1412804



Single locking latch for B10 housing, HC-EVO...AL and HC-STA...AL

---

### Labeled device marker

Plastic label - US-EMLP (20X9) CUS - 0830085



Plastic label, can be ordered: By card, white, labeled according to customer specifications, Mounting type: Adhesive, Lettering field: 20 x 9 mm

---

### Seal

Profile gasket - HC-B16-SP-CBK - 1411480



Profile gasket for HEAVYCON EVO supporting base element type B16, conductive