



JKL LAMP PART NO.	COLOR RGB WHITE REF. 9700°k	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS) MINIMUM
BF20185-25B	x = 0.28 ± 0.02 y = 0.26 ± 0.02	1050 @ 0°C	420	5	35,000 TYP.	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

NOTE 1: MERCURY (Hg) CONTENT: 2.4mg/LAMP MAX.

 THIRD ANGLE PROJECTION	DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0.2 2 PL +/- 0 ANGLE +/- 0	JKL COMPONENTS CORPORATION			
		TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP			
DRAWN BY L. WENGSTROM	APPVD BY L.R.	DATE 7/30/09	SIZE A	FSCM NO. 55335	DRAWING NO. BF20185-25B
- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED			SCALE NONE	RELEASED DATE 11/23/05	REVISION DATE 7/30/09
REV. NO.	DESCRIPTION/ECO NUMBER	APPVD DATE	REV. NO.	SHEET	1 OF 1