



Material
 Item a Clamp: Brass(CuZn), Ni plated
 Item b Terminal screw: Steel Zinc plating "-" slot type
 Item c Female contact: PbZr(CuSn)Tin plated
 Item d Terminal housing: Thermoplastic (UL94V-0)
 GREEN(RAL6018/T)

Electrical cULus
 Voltage rating: 300V
 Current rating: 10A
 Wire range:
 Solid wire(AWG): 16-28
 Stranded wire(AWG): 16-28
 Torque(Lb-In): 1.7Lb-In
 Screw: M2
 Wire strip length: 5-6mm
 Withstanding Voltage: 1.6KV
 Operating temperature: -40°C to +115°C
 Safety Approval: cULus

DIMENSION	
A	Nx3.81
B	(N-1)x3.81

N=Number of poles

Poles	Dim A&B Tol.
2p-6p	±0.15
7p-12p	±0.25
13p-16p	±0.35
17p-24p	±0.40

RoHS compliant
 Unit: mm

 File No.: E349947

Scale	Free
TOLERANCE	
X.	±0.50
X.X	±0.30
X.XX	±0.10
DIM TOL	
X.°	±1°
Angle	TOL

Id.	Modification	Date	Name
①	Add UL	18.04.2016	Amy
②	Drawn	19.04.2010	Alex

Date	Name
19.04.2010	Alex
18.04.2016	Amy

ASSMANN
 WSW components

Customer-No.	Drawing-No.	Replace
ASSMANN WSW-No.	A-TB381-THXX	
	ASS 4116 CO	rev01
		Sheet

1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	B
1	2	3	4	5	6	7	C
1	2	3	4	5	6	7	D
1	2	3	4	5	6	7	E
1	2	3	4	5	6	7	F
1	2	3	4	5	6	7	G
1	2	3	4	5	6	7	H