

REPLACES 206 566400-1

THIS DRAWING IS A CONTROLLED DOCUMENT.

RELEASED FOR PUBLICATION JULY, 1986.

**APPLICATOR PARTS LIST**

TYPE  
LENGTHWISE  
RING  
AMPLIFIER  
STUD RETAINING

AMP INCORPORATED  
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER	1	3-456408-3	42			
2	INS. CRIMPER			43			
3	ANVIL	1	473405-9	44			
4	ANVIL SPACER			45			
5	SHEAR BLADE	1	4-465233-1	46			
6	REAR SHEAR PLATE	1	385013-4	47			
7	SHEAR BLADE SPACER	2	373072	48			
8	FRONT SHEAR PLATE	1	810490-1	49			
9	REAR ANVIL SPACER PLT.	1	374769	50			
10	FRONT ANVIL SPACER PLT.	1	370483	51			
11	TOOL SPACER	1	385105	52			
12	CRIMP SPACER			53	HOLD DOWN BRACKET	1	811065-1
13	FRONT STRIP GUIDE	1	1-472438-9	54			
14	REAR STRIP GUIDE	1	2-472438-0	55			
15	RAM	1	471167	56			
16	TOOL HOLDER	1	376046	57			
17	ADJ. CRIMP MOUNT			58			
18	ADJ. BLOCK			59			
19	APPLICATOR MOUNT	1	570656	60			
20	BASE PLATE			61			
21	BASE BLOCK			62			
22	STRIP GUIDE PLATE			63			
23	ANVIL HOLDER	1	370526	64			
24	AUX. ANVIL HOLDER	1	377515	65	TENSION ADJ. PLATE	1	374999
25	STRIPPER	1	810872-1	MISCELLANEOUS			
26	STRIPPER MOUNT	1	386231	66	LUBRICATOR BSSY	1	465184-2
27	RETAINER PLATE	1	372251	67	TERMINAL LUBRICANT	1	22014-1
28	STRIPPER MOUNT BRACKET			68			
29	STRIPPER BUSHING			69			
30	STOCK DRAG	1	375381	70			
31	STOCK DRAG HANDLE			71			
32	STOCK DRAG STUD	2	354045-1	72			
33	STOCK DRAG SPRING	2	1-23847-1	REVISION RECORD			
34	STOCK DRAG ADJ. SCREW	2	372977	REV.	REVISION RECORD	DATE	BY
35	FEED FINGER HOLDER						
36	FEED FINGER	1	375093	D	0150-8890-98	10/98	UC
37	FEED FINGER TIP			C	0150-6442-25	10/95	UC
38	FEED FINGER SPACER			B	ECN A-395892	9-92	NO TB
39	BASE CASTING	1	570238	A	ADDED TERM 305076	9/26/83	83209
40	GUARD	1	4576647	A1	REV PER ECN	9-12-80	82684
41				A	REV PER ECN	6-6-78	82544

CRIMPING DATA

TO APPLY TERMINAL	WIRE SIZE	CRIMP HEIGHT	TERMINALS
	20	.054	505017
	18	.057	505075
	16	.062	
	19+20	.061	WITH LET 505072 305076

CRIMP SIZE TYPE FEED

WIRE 1/10 F 1.000

INSUL. — — —

SLEEVED — — —

MAGNET WIRE-WIRE RANGE 1000-2600 CM19

EXPLODED VIEW A-6000 A-6000-1

REMARKS:  
**REAR STRIP MUST BE ADJUSTED TO RUN DIFFERENT TERMINALS.**

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

■ DENOTES WEARING PARTS  
 ■ RECOMMEND PURCHASE REPLACEMENT

THIS APPLICATOR IS TO BE USED ON  
 AMP-O-ELECTRIC 1-471273-3  
 AMP-O-MATIC

ALIGN BA. 679597-1

SERIAL NO. DATE SHIPPED

CUSTOMER NAME AND ADDRESS

DESIGNED: 12/2/75

CHK'D: 1-18

APPLD: 1-78

APPLICATOR REV. 566260-1 SHEET 1 OF 1

CAGE CODE 00779 CUSTOMER AND ASSEMBLY DRAWING RESTRICTED TO

OR MAKE CHANGE SEE 5-6-87200-5

THIS DRAWING IS A CONTROLLED DOCUMENT.

RELEASED FOR PUBLICATION JULY, 1986.

BY AMP INCORPORATED. ALL RIGHTS RESERVED.

COPYRIGHT 1986