

Main

Body type	Standard
Contact block name	XE2SP2151
Device short name	XCKJ
Range of Product	OsiSense
Series name	Heavy duty

Complementary

[I _{th}] conventional free air thermal current	10 A
Associated head	ZCKE05
Body Material	Metal
Contact operation	Snap action
Height	5.39 in (137 mm)
Positive opening	With
Product Weight	1.07 lb(US) (0.49 kg)
Switch actuation	CW and CCW
Torque Value	33.3 ozf.in
Type of operator	Spring return rod lever steel round rod 3 mm

Environment

Ambient Air Temperature for Operation	-13...158 °F (-25...70 °C)
IP Degree of Protection	IP66
NEMA Degree of Protection	NEMA 1/2/4/12
Product Certifications	CSA UL Listed CE
Shock resistance	50 gn
Standards	CENELEC EN 50041
Vibration resistance	25 gn 10...500 Hz)

Ordering and shipping details

Category	22411-LIMIT SWITCHES,IEC,XCKJ
Discount Schedule	T
GTIN	3389119082945
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	11.20 oz (317.515 g)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------