



specifications

Consumption	Voltage	CRI	Base	Lens	Heat Sink	L70 hours	Ambient Temp (F)	Power Factor	Mounting	THD	Beam Angle	Enclosed Fixture Rated
24W 3 strips	⚡ 100-277 V	83	hard-wire	frosted polycarbonate	aluminum	50,000	-4 - 104°	>0.9	magnetic strip screws	<25%	120°	yes

*select your lamp

Part Number	Color Temp	Dimmable	Efficacy	Lumens
GI-23TRK-W50DC-UL4	3000K ⚡	0-10 V	132.7 lm / w	3,184.3
GI-23TRK-W50C-UL4	3500K ⚡	no	132.7 lm / w	3,184.3
GI-23TRK-D50C-UL4	4000K ⚡	no	132.7 lm / w	3,184.3
GI-23TRK-C50C-UL4	5000K ⚡	no	132.7 lm / w	3,184.3

other

Dimensions	Warranty	Case QTY
2 ft	6 years	30 pcs



included driver



Features

- ▶ Does not need tombstones; hard-wired
- ▶ 50,000 hour LED lifespan based on IES LM-80 results and TM-21 calculations
- ▶ External driver
- ▶ Can be installed using included screws or magnetic backing



Not all product variations listed on this page may be DLC qualified. Visit www.designlights.org/search to confirm qualification.

