

## OMNIMATE Power - series WGK WGK 50/Z GN/YE

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



The WGK finger-proof-insulated enclosures are especially suitable as industrial electronic enclosures for frequency converters, power supplies or filter components which offer a convenient and reliable form of connection internally and externally.

### General ordering data

Order No.	<a href="#">1937100000</a>
Type	WGK 50/Z GN/YE
Version	OMNIMATE Power - series WGK, Feedthrough terminal, Rated cross-section: 50 mm <sup>2</sup> , Screw connection, green / yellow, Direct mounting, Feedthrough (bushing)
GTIN (EAN)	4032248664634
Qty.	10 pc(s).

**OMNIMATE Power - series WGK  
WGK 50/Z GN/YE**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**
**Dimensions and weights**

Length	78 mm	Width	18.8 mm
Height	55 mm	Height of lowest version	55 mm
Net weight	98.25 g		

**2 clampable conductors with identical cross-section**

Wire connection cross section AWG, max.	AWG 1/0	Wire connection cross section AWG, min.	AWG 6
---	---------	---	-------

**Additional connection**

Blade size	1.2 x 8.0 mm	Clamping screw	M 6
Rated current	150 A	Tightening torque, max.	6.5 Nm
Tightening torque, min.	4 Nm		

**Conductors suitable for clamping**

Cross-section for connected conductor, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, min.	10 mm <sup>2</sup>	Twin wire-end ferrules, max.	10 mm <sup>2</sup>
Twin wire-end ferrules, min.	6 mm <sup>2</sup>	Wire connection cross section AWG, max.	AWG 1/0
Wire connection cross section AWG, min.	AWG 6	Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, max.	50 mm <sup>2</sup>
Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, rated connection, min.	10 mm <sup>2</sup>	Wire connection cross section, finely stranded, max.	50 mm <sup>2</sup>
Wire connection cross section, solid core max. rated connection	16 mm <sup>2</sup>	Wire connection cross section, stranded, rated connection, max.	50 mm <sup>2</sup>
Wire connection cross section, stranded, rated connection, min.	16 mm <sup>2</sup>	Wire connection cross-section, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, max.	50 mm <sup>2</sup>
Stripping length	24 mm		

**Rated data to IEC**

Current at maximum wires	150 A	Pollution severity	3
Rated cross-section	50 mm <sup>2</sup>	Rated current	150 A
Rated impulse withstand voltage	8 kV	Rated voltage	690 V
Standards	IEC 60947-7-1		

**Technical data**

Blade size	1.2 x 8.0 mm	Clamping range, rated connection, max.	50 mm <sup>2</sup>
Clamping range, rated connection, min.	13.3 mm <sup>2</sup>	Clamping screw	M 6
Gauge to IEC 60947-1	B10	Number of connections	2
Stripping length, rated connection	24 mm	Tightening torque, max.	6.5 Nm
Tightening torque, min.	4 Nm		

**OMNIMATE Power - series WGK  
WGK 50/Z GN/YE**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Technical specification**

Colour of insulating material	green / yellow	Connection direction	on side
End cover plate required	No	Installation advice	Direct mounting, Feed-through (bushing)
Product family	OMNIMATE Power - series WGK		

**CSA ratings data**

Certificate No. (CSA)	200039-1830694	Wire cross section min. (CSA)	6 AWG
-----------------------	----------------	-------------------------------	-------

**UL ratings data**

Certificate No. (cURus)	E60693VOL1SEC84	Conductor size Factory wiring min. (cURus)	6 AWG
Conductor size Field wiring min. (cURus) 6 AWG			

**Material data**

Material	Wemid	Colour	Green, Yellow
UL 94 flammability rating	V-0		

**Classifications**

ETIM 3.0	EC001283	UNSPSC	30-21-18-11
eClass 5.1	27-14-11-34	eClass 6.2	27-14-11-34
eClass 7.1	27-14-11-34		

**Notes**

Notes	• Metal walls: 1 - 2.5 mm = 800 V; 2.5 - 6 mm = 690 V; plastic walls: 1 - 6 mm = 800 V
-------	--

**Approvals**

Approvals



ROHS	Conform
------	---------

**OMNIMATE Power - series WGK  
WGK 50/Z GN/YE**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Drawings**

