

MICRO SWITCH SAFETY SWITCH COMPARISON

DESIGN	CABLE PULL				MECHANICAL ACTUATION			KEY ACTUATION			
SERIES	2CCP	1CPS	2CPS	CLSX	GSX	GSA	924/24CE	GK	GKE	GKM	GKN
											
Typical applications	Conveyor systems, perimeter guarding, packaging equipment, assembly lines				Position detection, mechanical travel limits, drift detection, machine tools, material handling, doors, apertures			Doors, apertures, safety interlock, cabinet power isolation, and guard detection			
Certifications	UL, cUL, CE, UKCA, SIL3	UL, CSA, CE, UKCA, SIL3	UL, CSA, CE, UKCA, SIL3	UL, CSA	cULus, CE, UKCA, IEC Ex, INMETRO, KOSHA, SIL3	UL, CSA, CE, UKCA, SIL 3	CE, UKCA, cULus, SIL3	UL, CSA, CE, UKCA, SIL 3	cULus, CE, UKCA, SIL3	UL, CSA, CE, UKCA, SIL3	cULus, CE, UKCA, CCC, SIL3
Mounting centers (mm)	172,7 x 50,8	152 x 72	139 x 104	120 x 30	120 x 30	30 x 60	25	30 x 60	20	22	40
Housing	Aluminium	Zinc	Zinc	Aluminium	Aluminium	Zinc	Zinc	Zinc	Polyester	Polyester	Polyester
Body dimensions (l x w [depth] x h (mm))	187 x 60 x 127	99 x 50 x 172	140 x 66 x 152	154 x 76 x 72	154 x 76 x 72	121 x 42 x 42	49 x 40 x 16	121 x 42 x 42	95 x 30 x 33	69 x 34 x 16	90 x 64 x 30
Environmental sealing	NEMA 1; IP54	NEMA 1, 4, 13; IP67	NEMA 1, 4, 12, 13; IP67	NEMA 1, 3, 4, 13; IP67	NEMA 1, 3, 4, 12, 13; IP67	NEMA 1, 4, 12, 13; IP66 & IP67	IP66	NEMA 1, 4, 12, 13; IP67	NEMA 1, 4X (indoor only), 12, 13; IP66/67	IP67	NEMA 1, 4X (indoor only), 12, 13; IP67
Operating temperature	-40 °C to 85 °C	-40 °C to 80 °C	-40 °C to 80 °C	1 °C to 70 °C	-40 °C to 70 °C	-25 °C to 85 °C	0 °C to 70 °C (-40 °C optional)	-25 °C to 85 °C	-25 °C to 85 °C	-25 °C to 85 °C	-25 °C to 70 °C
Circuits	2NC/2NO 3NC/1NO 4NC	1NC/1NO 2NC/2NO 3NC/1NO 4NC	1NC/1NO 2NC/2NO 3NC/1NO 4NC	1NC 1NC/1NO 2NC 1NO/3NC 2NO/2NC	1NC/1NO 1NC/1NO BBM 1NC/1NO MBB 2NC 2NC/2NO 4NC slow 2NC/1NO BBM 2NC/2NO BBM 3NC/1NO BBM	1NC/1NO 1NC/1NO BBM 1NC/1NO MBB 2NC 2NC/2NO 4NC slow 2NC/1NO BBM 2NC/2NO BBM 3NC/1NO BBM	1NC/1NO BBM 1NC/1NO MBB 1NC	1NC/1NO snap 2NC/2NO snap 1NC/1NO BBM 1NC/1NO MBB 2NC/1NO BBM 2NC/2NO BBM 3NC/1NO BBM 2NC 4NC	1NC/1NO snap 1NC/1NO BBM 2NC slow	1NC/1NO BBM 2NC	2NC/1NO slow 3NC Slow
Electrical	10A th AC15, A300 DC13, Q300	10A th AC15, A300 DC13, Q300	10A th AC15, A300 DC13, Q300	10A th 24 Vdc, 250 Vdc 120 Vac, 240 Vac, 600 Vac	10A th AC15, A300/A600; DC13, Q300	10A th AC15, A300/A600; DC13, Q300	10A th AC15, B300; DC13, R300	10A th AC15, A300/A600; DC13, Q300	10A th AC15, A300/A600; DC13, Q300	5A/2A th AC15, A300; DC13, Q300	10A th AC15, A600; DC13, Q300
Positive opening NC contacts	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes	yes
Connection	Conduit	Conduit	Conduit	Conduit	Conduit	Conduit	Pre-Cabled/Connector	Conduit/Connector	Conduit	Pre-Cabled	Conduit
Contacts	Silver	Silver, Gold	Silver, Gold	Silver, Gold	Silver, Gold	Silver, Gold	Silver	Silver, Gold	Silver	Silver, Gold	Silver
Hazardous approvals	-	-	-	NEMA 7, Class I Div 1 & 2 Groups B, C, D NEMA 9, Class II Div 1 & 2 Groups E, F, G	Class I (Flammable Gas) Div 1 & 2, Groups B, C, D Class II (Combustible Dust) Div 1 & 2, Groups E, F, G Class III (Combustible Fibers and Filings) Div 1 & 2 ATEX, IEC Ex, INMETRO II 2GD Exd IIC T6 Gb Ext III C IP6X T85°C Db (Tamb -40°C to 70°C)	-	-	-	-	-	-

Honeywell Advanced Sensing Technologies

830 East Arapaho Road
Richardson, TX 75081
800-582-4263
sps.honeywell.com/ast

004794-3-EN | 3 | 06/21
© 2021 Honeywell International Inc. All rights reserved.

Find out more

Honeywell Sensing and Internet of Things services its customers through a worldwide network of sales offices and distributors. For application assistance, current specifications, pricing, or the nearest Authorized Distributor, visit sensing.honeywell.com or call: International +815 618 3231; USA/Canada +302 613 4491

Honeywell