



Notes:

1. Electrical:
 - Meets EIA/TIA-568-B.2-10 Cat. 6A Channel Specification
 - Connector Operating Temperature: -40° C to +85° C
2. Materials and Finish:
 - Coupling Ring: Brass, Nickel Plated
 - Ⓟ - Plug Housing: Zinc Die-Cast, Nickel Plated
 - Interfacial Seal: Silicon, Color: White
 - Cable Gland: Brass, Nickel Plated
 - Cable Gland Seal: NBR, Color: Black
 - Cat.6A RJ45 Plug Metal Shell: Copper Alloy, Nickel Plated
 - Cat.6A RJ45 Plug Plastic Housing: Clear Polycarbonate UL94 V-2
 - Cat.6A RJ45 Plug Contacts: Phosphor Bronze, Finish: 50 u" Gold min. over Nickel
 - Cable: Cat.6A SSTP, 4 Pairs, AWG26, Stranded, Jacket Color: Black

RoHS Compliant

Ⓞ Patch Cord Length L	Part Number
1m ± 0.02m	17-180584
2m ± 0.03m	17-150794
3m ± 0.03m	17-180594
4m ± 0.04m	17-150804
5m ± 0.05m	17-150814
10m ± 0.10m	17-180604
20m ± 0.20m	17-180614

*Note: Special cable length and blue cable up to 20m are available please contact factory
Cable length > 20m cannot guarantee to meet TIA/EIA-568-C.2 Cat. 6A Specification.

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION OF CONEC CORPORATION OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION DOT NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale: NTS	Dim. in meter
	Name	Title	Approval Date	0 PLC ±0.50	1 PLC ±0.38		Autodesk Inventor Material: See Notes	Cat. 6A RJ45 Ethernet Patch Cords IP67 Industrial to IP67 Industrial Hex 32, M28 Thread Metal Version
				2 PLC ±0.25	3 PLC ±0.10			
				ANGES	±3°			
				2011	Date	Name	Drawing No.: 17K1A290	DIN A3
			Draw.	Sept. 28	Vincent Ke			
				Appd.	Sept. 28	J. Chaudry	Part No.: SEE PART NUMBER TABLE	
				Norm				
	c	1 x c	Apr/15/2015	Vincent Ke	D-old		Sheet 1/1	
	b	1 x b	Jun/23/2014	Vincent Ke				
	a	original						
	Rev.	Changes	Date	Name				