

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
1	RE-H-03367	M.K.C.H	99.11.05						
APPLICABLE STANDARD									
RATING OPERATING TEMPERATURE RANGE: -35 °C TO +85 °C(NOTE1) VOLTAGE: 100 V AC CURRENT: AWG28:1 A AWG30:0.5A				STORAGE TEMPERATURE RANGE : -10 °C TO +60 °C APPLICABLE CONTACT : ADF20B-2830SCFA APPLICABLE CONNECTOR : DF20*- *DP-1* APPLICABLE CABLE : 28-30AWG JACKET DIAMETER : 0.6MAX					
SPECIFICATIONS									
ITEM		TEST METHOD			REQUIREMENTS			QT	AT
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT			ACCORDING TO DRAWING			○	○
MARKING		CONFIRMED VISUALLY						○	○
ELECTRICAL CHARACTERISTICS									
CONTACT RESISTANCE		100 mA (DC OR 1000 Hz)			mΩ MAX			-	-
CONTACT RESISTANCE		20 mV MAX. mA(DC OR 1000 Hz)						-	-
MILLIVOLT LEVEL								-	-
METHOD								-	-
INSULATION RESISTANCE		V DC.			MIN.			-	-
VOLTAGE PROOF		V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN.			-	-
MECHANICAL CHARACTERISTICS									
CONTACT INSERTION AND EXTRACTION FORCES		BY STEEL GAUGE.			INSERTION FORCE: N MAX. EXTRACTION FORCE: N MIN.			-	-
INSERTION AND WITHDRAWAL FORCES		MEASURED BY APPLICABLE CONNECTOR			INSERTION FORCE: N MAX. EXTRACTION FORCE: N MIN.			-	-
MECHANICAL OPERATION		TIMES INSERTION AND EXTRACTION.			① CONTACT RESISTANCE: mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			-	-
VIBRATION		FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h FOR 3 DIRECTIONS.			① NO ELECTRICAL DISCONTINUITY OF 1 μs			○	-
SHOCK		490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.			② CONTACT RESISTANCE: mΩ MAX. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			○	-
ENVIRONMENTAL CHARACTERISTICS									
RAPID CHANGE OF TEMPERATURE		TEMPERATURE -55 → 5~35 → +85 → 5~35 °C TIME 30 → 2~3 → 30 → 2~3 min UNDER 5 CYCLES.			① CONTACT RESISTANCE: 30 mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.			○	-
DAMP HEAT(STEADY STATE)		EXPOSED AT 40 ± 2 °C, 90 ~ 95 % 96 h.			① CONTACT RESISTANCE: mΩ MAX.			○	-
CORROSION, SALT MIST		EXPOSED IN 5 % SALT WATER SPRAY FOR 48 h			① CONTACT RESISTANCE: mΩ MAX. ② NO HEAVY CORROSION			○	-
HYDROGEN SULPHIDE		EXPOSED IN PPM FOR h (TEST STANDARD: JEIDA-38)			① CONTACT RESISTANCE: mΩ MAX. ② NO HEAVY CORROSION			-	-
SULPHUR DIOXIDE		EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD: JEIDA-39)			① CONTACT RESISTANCE: mΩ MAX. ② NO HEAVY CORROSION			○	-
RESISTANCE TO SOLDERING HEAT		SOLDER TEMPERATURE, °C, FOR IMMERSION DURATION, s.			NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.			-	-
SOLDERABILITY		SOLDERED AT SOLDER TEMPERATURE, °C, FOR IMMERSION DURATION, s.			SOLDER SHALL COVER A MINIMUM OF 95 % OF THE SURFACE BEING IMMersed.			-	-
REMARKS NOTE 1: INCLUDE THE TEMPERATURE RISING BY CURRENT.									
DRAWN		DESIGNED		CHECKED		APPROVED		RELEASED	
H UMEHARA		H UMEHARA		M NAKAMURA		K KATAYOSE			
98.11.13		98.11.13		98.11.16		98.11.16			
Unless otherwise specified, refer to MIL-STD-1344.									
Note ○T Qualification Test AT Assurance Test ○ Applicable Test									
HS HIROSE ELECTRIC CO., LTD. SPECIFICATION SHEET									
CODE NO (OLD)		DRAWING NO		PART NO		PART NO			
CL		ELC4-162771		CL 6 8 6		DF20A-*DS-1C		1	
TO								1	