



Pin	Dim.(mm)		Order Code
	A	B	
2X05	4.00	8.00	M40-1200500
2X06	5.00	9.00	M40-1200600
2X07	6.00	10.00	M40-1200700
2X08	7.00	11.00	M40-1200800
2X09	8.00	12.00	M40-1200900
2X10	9.00	13.00	M40-1201000
2X12	11.00	15.00	M40-1201200
2X15	14.00	18.00	M40-1201500
2X20	19.00	23.00	M40-1202000
2X25	24.00	28.00	M40-1202500

SPECIFICATIONS:

MATERIAL(HALOGEN FREE):

NYLON 66, UL94V-0 (WHITE)

ELECTRICAL:

CURRENT RATING: 1A AC/DC

VOLTAGE RATING: 50V AC/DC

WITHSTAND VOLTAGE: 500V AC/MINUTE

CONTACT RESISTANCE: 20 mΩ MAX.

INSULATION RESISTANCE: 100 MΩ MIN.

ENVIRONMENTAL:

TEMPERATURE RANGE: -25°C TO +85°C

ORDER CODE

M40-120 XX 00

NO. OF WAYS PER ROW

Leo	3	08.02.18	A530
Allan	2	03.05.07	A041
Allan	1	01.08.06	--

NAME	ISS.	DATE	C/NOTE
------	------	------	--------

APPROVED: B.Lim

CHECKED: D.P

DRAWN: Leo

CUSTOMER REF.:

ASSEMBLY DRG:

NOTE: ALL DIMENSIONS AND NOTES MARKED * ARE CRITICAL AND MUST BE CHECKED IN ACCORDANCE WITH QUALITY DOC. QI-02A

HARWIN

HARWIN USA
TEL: 603 893 5376
FAX: 603 893 5396
mis@harwin.com

HARWIN Europe (UK)
TEL: 023 9231 4545
FAX: 023 9231 4590
mis@harwin.co.uk

HARWIN Asia
TEL: +65 6 779 4909
FAX: +65 6 779 3868
mis@harwin.com.sg

THIS DRAWING AND ANY INFORMATION OR DESCRIPTIVE MATTER SET OUT HEREON ARE CONFIDENTIAL AND COPYRIGHT PROPERTY OF THE HARWIN GROUP AND MUST NOT BE DISCLOSED, LOANED, COPIED OR USED FOR MANUFACTURING, TENDERING OR FOR ANY OTHER PURPOSE WITHOUT THEIR WRITTEN PERMISSION.

TOLERANCES
X. = ±0.30mm
X.X = ±0.25mm
X.XX = ±0.15mm
X.XXX = ±0.08mm
ANGLES = ±3°
UNLESS STATED

MATERIAL: SEE NOTES

FINISH: SEE NOTES

S/AREA: mm²

TITLE:
1.00mm PITCH WIRE TO BOARD CONNECTOR

DRAWING NUMBER:
M40-120 XX 00

SHT
1
OF
1