



SIGN	DATE	DESCRIPTION	APPROVER

- Material:
- Insulator(housing): Thermoplastic (UL94V-0)
 - Terminal Body: Brass
 - Contact: PhBz.
 - Wire guard: Stainless steel
 - Terminal Screw: Steel zinc plated.

- Electrical: UL
- Voltage rating: 300 V
 - Current rating: 32 A
 - Wire range:
 - Solid wire(AWG): 8-24
 - Stranded wire(AWG): 8-24
 - Torque: 7 Lb-In
 - Screw: M3.5
 - Wire strip length: 7-8 mm
 - Withstanding Voltage: 2.2KV
 - Operating temperature: -33°C to +105°C
 - Safety Approval: US

RoHS Compliant

PART NUMBER:

OSTETXX0250

No. of Poles	COLOR
02 2 Poles	0: Black
03 3 Poles	5: Green (Standard)
... ..	6: Blue
16 16 Poles	8: Grey

POLE	2	3	4	5	6	7	8	
Dim L	15.24	22.86	30.48	38.10	45.72	53.34	60.96	
Dim P	7.62	15.24	22.86	30.48	38.10	45.72	53.34	
Tol.	±0.10			±0.15				
POLE	9	10	11	12	13	14	15	16
Dim L	68.58	76.20	83.82	91.44	99.06	106.68	114.30	121.92
Dim P	60.96	68.58	76.20	83.82	91.44	99.06	106.68	114.30
Tol.	±0.20				±0.30			



TITLE								OSTET-7.62 Series (Mated with OSTVC series)	
PART NO.		OSTETXX0250			DWG NO.		OSTETXX0250.DWG		
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance		
			Tony 2007.03.09	Tony 2007.03.09			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°		
						UNIT: mm SCALE: NONE		SHEET: 01/01 REV: B	