





## WRIST STRAP:

- A. Stamped 4mm (nominal) stud. To fit 4mm (nominal) spring loaded medical snap socket.
- B. Easy to open plastic clasp secures elastic material in place, and allows the user to easily adjust the wrist band size. Maintains electrical continuity even when open.
- C. Non-allergenic stainless steel base plate, provides excellent skin contact, for superior grounding.
- D. Insulating cap, thermoplastic.
- E. Soft elastic band.

**Band Circumference:** 

Min: 3" 76mm Max: 15" 381mm Width: 0.75" 19mm

## **GROUND CORD:**

- F. Barrel type banana plug. Fits industry standard banana jack 4.22mm (nominal).
- G. Metallized, high flex tinsel, black jacket.
- H. Alligator clip included.
- Spring loaded snap socket.
- J. One megohm, resistor, molded within snap assembly, limits current for operator safety.

\*The color of the band material may vary.\*

	Item	Description
	<u>23311</u>	Wrist Strap, Economy, Adjustable, 12 ft Cord, 4mm
	23312	Wrist Strap, Economy, Adjustable, 6 ft Cord, 4mm

Specifications and procedures subject to change without notice

## Wrist Strap, Adjustable, Economy

ESD SYSTEMS.com

ESD SYSTEMS.COM 432 NORTHBORO ROAD CENTRAL MARLBORO, MA 01752 USA TEL. (508) 485-7390 FAX (508) 480-0257

DRAWING NUMBER
TD-23311

May 2010