SIEMENS

Data sheet

US2:52BP2J2



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Transformer type, 480V AC Incandescent Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Black with Red Lens 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Actuator round Enclosure 1 delivery state as a kit No Actuator product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes geraduct component front ring Yes design of the front ring metal color of the front ring metal color of the front ring Bada Holder Metal Contract tock/is lampholder 0 contract tock/is lampholder 0 General tochical data Yes elight source AC of the coperating voltage AC of		
number of command points 1 delivery state as a kit No Actuator	design of the product	Actuator round
delivery state as a kit No Actuator product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device publicounlatch mechanism publicounlatch mechanism test product component front ring yes standard material of the front ring standard metal color of the front ring black black Holder metal color of the front ring black Holder material of the holder Metal color of the front ring black Holder metal of the holder Metal colorate thock/ lampholder socket design no socket design BA 9s with lamp number of LED modules 0 colorate thock/ lampholder socket design <	Enclosure	
Actuator yreduct extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device pulk-to-unlatch mechanism number of switching positions 2 Front ring yes design of the front ring Yes design of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder socket design mumber of LED modules 0 General technical data product component product component Yes eight source Yes degree of pollution 1 type of voltage AC e of the loperating voltage AC e of the input voltage AC surger voltage resistance rated value 4 kV protection class IP IP66 e of the input voltage of the light source AC	number of command points	1
product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes design of the front ring Metal color of the optal metal color of the optal metal color of the optal metal of the inpul voltage AC	delivery state as a kit	No
material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes design of the front ring Standard material of the front ring metal color of the front ring black Holder Metal Contact block/lampholder Sockat design sockat design BA 9s with lamp number of LED modules 0 General technical data Impholder product component I i light source Yes e light source Yes e of the loperating voltage AC of the terminal IP20 Support voltage AC of the terminal IP20 Supply voltage of the light source at AC at 60 Hz 6 V output voltage 1 of the lamp transformer rated value 6 V	Actuator	
type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring product component front ring Yes design of the front ring standard metal color of the front ring black Holdor material of the holder Metal Contract block/ lampholder socket design BA 9s with lamp metal number of lampholders 1 Display number of LED modules 0 Contract block/ lampholder elight source Yes Yes elight source Yes Contract block/ lampholder socket design 0 Contract block/ lampholder number of LED modules 0 Contract block/ lampholder elight source Yes Secket design of the operating voltage AC Secket design of the operating voltage AC Contract block/ lampholder surge voltage resistance rated value 4 kV Protection class IP of the operating voltage AC Secket design of the terminal	product extension optional light source	Yes
number of switching positions 2 Front ring yes design of the front ring standard material of the front ring metal color of the front ring black Holder metal material of the holder Metal Contact block/ lampholder socket design number of lampholders 1 Display Interplay number of LED modules 0 General technical data Front.us product component Interplay i light source Yes of the operating voltage AC of the input voltage AC of the input voltage AC surge voltage resistance rated value 4 kV product class IP IP66 i of the terminal IP20 Supply voltage of the light source AC surge voltage resistance rated AC at 60 Hz 6 V i nputa/Outputs 6 V	material of the actuating element	metal mushroom head with plastic lens
Front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder metal color of the front ring black Holder Metal Contact block/lampholder socket design socket design BA 9s with lamp number of LED modules 0 General technical data 0 General technical data	type of unlocking device	pull-to-unlatch mechanism
product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder black material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data on product component Ves e light source Yes degree of pollution 1 type of voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 e of the terminal IP20 Supply voltage of the source at AC at 60 Hz 6 V inputs/ Outputs 6 V	number of switching positions	2
design of the front ring standard material of the front ring metal color of the front ring black Holdor material of the holder material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with lamp number of lampholders 1 Display	Front ring	
material of the front ring metal color of the front ring black Holder material of the holder material of the holder Metal Contact block/lampholder socket design socket design BA 9s with lamp number of lampholders 1 Pisplay 0 General tachnical data product component • lamp transformer Yes • light source Yes • degree of pollution 1 type of voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of voltage of the light source AC supply voltage AC supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs	product component front ring	Yes
color of the front ring black Holder material of the holder material of the holder Metal Contact block/ lampholder socket design number of lampholders 1 Display 0 General technical data 0 gene	design of the front ring	standard
Holder Metal Contact block/lampholder BA 9s with lamp socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 general technical data Ves elight source Yes elight source Yes degree of pollution 1 type of voltage AC of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage of the light source at AC at 60 Hz 6 V erated value 6 V Inputs/ Outputs output voltage 1 of the lamp transformer rated value	material of the front ring	metal
material of the holder Metal Contact block/ lampholder socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 product component • • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC • value 6 V Inputs/Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	color of the front ring	black
Contact block/ lampholder socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 degree of pollution 1 type of voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V	Holder	
socket design BA 9s with lamp number of lampholders 1 Display 0 General technical data 0 general technical data 0 product component 0 • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage 0 • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	material of the holder	Metal
number of lampholders 1 Display 0 General technical data 0 general technical data 0 product component Yes • light source Yes • light source Yes • degree of pollution 1 type of voltage AC • of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	Contact block/ lampholder	
Display 0 number of LED modules 0 General technical data 0 product component 0 e lamp transformer Yes e light source Yes degree of pollution 1 type of voltage AC of the operating voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz AC orated value 6 V Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V	socket design	BA 9s with lamp
number of LED modules 0 General technical data	number of lampholders	1
General technical data product component • lamp transformer Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	Display	
product component Yes elamp transformer Yes elight source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the light source AC supply voltage AC output voltage of the light source AC supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V e rated value 6 V Inputs/ Outputs 6 V	number of LED modules	0
• lamp transformer Yes • light source Yes • light source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC • of the input voltage AC • of the input voltage IP66 • of the terminal IP20 Supply voltage AC supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	General technical data	
Ight source Yes degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V	product component	
degree of pollution 1 type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	lamp transformer	Yes
type of voltage AC • of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the supply voltage of the light source at AC at 60 Hz AC • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	light source	Yes
• of the operating voltage AC • of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	degree of pollution	1
• of the input voltage AC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage IP20 Supply voltage of the supply voltage of the light source AC supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	type of voltage	
surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage IP20 supply voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	 of the operating voltage 	AC
protection class IP IP66 • of the terminal IP20 Supply voltage IP66 type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 6 V	 of the input voltage 	AC
• of the terminal IP20 Supply voltage AC type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	surge voltage resistance rated value	4 kV
Supply voltage type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V	protection class IP	IP66
type of voltage of the supply voltage of the light source AC supply voltage of the light source at AC at 60 Hz 6 V • rated value 6 V Inputs/ Outputs 6 V output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 6 V	• of the terminal	IP20
supply voltage of the light source at AC at 60 Hz • rated value 6 V Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals	Supply voltage	
rated value 6 V Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals		AC
Inputs/ Outputs output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals	supply voltage of the light source at AC at 60 Hz	
output voltage 1 of the lamp transformer rated value 6 V Connections/ Terminals 6 V		6 V
Connections/ Terminals	Inputs/ Outputs	
		6 V
type of electrical connection screw-type terminals		
	type of electrical connection	screw-type terminals

 of modules and accessories 	Screw-type terminal
tightening torque of the screws in the bracket	20 N·m
tightening torque [lbf-in] with screw-type terminals	8 8 lbf·in
Lamp	
type of light source	filament lamp
color of the light source	clear
Safety related data	
touch protection against electrical shock	finger-safe
Ambient conditions	
ambient temperature	
during operation	-35 +70 °C
during storage	-40 +85 °C
Installation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-do Siemens is working on the renewal of the current EAC certifica	ates. i the EAC certification if you intend to import or offer to supply these products to an ates Russia or Belarus). =US2:52BP2J2 x?lang=en&mlfb=US2:52BP2J2 s,) models, device circuit diagrams, EPLAN macros,)

last modified:

5/31/2021 🖸