



5G/LTE Band 30 / WCS Band Downlink Connectorized Ceramic Band Pass Filter



ANATECH ELECTRONICS INC
RF & Microwave Filters & Products

Part Number: AE2355CB1791-C

Electrical Specifications

Center Frequency: 2355 MHz
3dB Bandwidth(BW): 10 MHz Min.
Passband Frequency (PB): 2350-2360 MHz
Insertion Loss in BW : 4.0 dB Max
Ripple In BW: 1.0dB Max.
Return Loss : 12 dB Min.
Rejection1: 30 dB Min.@ 2315 MHz
Rejection2: 10 dB Min. @ 2370 MHz
Power Handling: 1 W
Input / output Impedance: 50 Ohms


Mechanical

Mounting Method: Through Holes
Connector Type: SMA(F)
Dimensions: 50 x 45 x 17.5 mm

Environmental

Operating Temperature: -45°C to +85°C
Storage Temperature: -50°C to +90 °C
Shock: 10G. 11ms
Vibration: 10G 0.5 to 200 Hz

Outline Drawing:



TOLERANCE UNLESS
OTHERWISE SPECIFIED : ± 0.3
DIMENSION : mm

Tolerance: +/-0.01 inches [+/- 0.3mm]

Angles: +/- 1 Deg.

*Tolerance as shown unless otherwise specified in the datasheet electrical specification tables above.

*When max dimensions are called out the above tolerances do not apply as long as it is under the max call out.