

**PLUGSERIES  
PLED 24Vdc**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-2083  
www.weidmueller.com

High power/currents can be safely switched with the PLUGSERIES. The modular system enables conventional relays and LED indicators simply to be plugged in. Retaining and disassembly clips provide a secure mount. Pre-assembled relays with 1 or 2 changeover contacts and input voltages from 24V to 230V round of the product range. Plug-in ZQV 2.5 cross-connectors enable relay multiplexers to be set up quickly thanks to simple side-by-side mounting.

**General ordering data**

|                  |  |
|------------------|--|
| Order No.        | <a href="#">8536710000</a>   |
| Part designation | PLED 24Vdc   |
| Version          | PLUGSERIES, Relays, No. of contacts: Rated control voltage: Plug-in connection |
| GTIN (EAN)       | 4032248171972  |
| Qty.             | 20 pc(s).  |

## PLUGSERIES PLED 24Vdc

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-2083  
 www.weidmueller.com

## Technical data

### Dimensions

|        |       |
|--------|-------|
| Length | 92 mm |
|--------|-------|

### Temperature

|                                   |                 |                     |
|-----------------------------------|-----------------|---------------------|
| Ambient temperature (operational) | -40 °C...+50 °C | Storage temperature |
|-----------------------------------|-----------------|---------------------|

### Rated data

|                             |                    |                          |     |
|-----------------------------|--------------------|--------------------------|-----|
| Conductor connection system | Plug-in connection | Flammability class UL 94 | V-0 |
|-----------------------------|--------------------|--------------------------|-----|

### Insulation coordination (EN 50 178)

|                  |       |   |     |
|------------------|-------|---|-----|
| Protection class | IP 20 | Protective separation acc. to VDE 0106 part 101 | Yes |
|------------------|-------|---|-----|

### Other technical data

|         |   |
|---------|---|
| Version | Relay accessory - LED with free-wheel diode |
|---------|---|

### Approvals

|                      |    |
|----------------------|----|
| Approvals institutes | CE |
|----------------------|----|

### Classifications

|            |             |            |             |
|------------|-------------|------------|-------------|
| ETIM 2.0   | EC000996    | ETIM 3.0   | EC000996    |
| eClass 5.1 | 27-11-06-35 | eClass 6.0 | 27-11-06-35 |

### Notes

|                      |  |
|----------------------|--|
| Note, technical data | Cross-connectors and markers - refer to PLUGSERIES accessories |
|----------------------|--|