



(B)

- NOTES:
1. MATERIAL: AS NOTED
 2. FINISH: AS NOTED
 3. ELECTRICAL:
VOLTAGE: 600VAC
CURRENT: 25A
 4. TEMP RATING: -20°C TO +90°C
 5. CSA CERTIFIED FILE: LR6837
 6. UL RECOGNIZED FILE: E46237
 7. ALL DIMS ARE FOR REFERENCE UNLESS TOLERANCED OR NOTED OTHERWISE

MATERIAL NO.	ENGINEERING NO.	CHAIN LENGTH
1300190003	22803	1 FT. (0.31 M)
1300190004	22804	2 FT. (0.61 M)
1300190005	22805	3 FT. (0.91 M)

ITEM	DESCRIPTION	MATERIAL	FINISH
5	CHAIN	STEEL	ZINC PLATE
4	YOKE	STEEL	ZINC PLATE
3	#10 X 1/2 RD HD DRIVE SCREW	STEEL	ZINC PLATE
2	SPACER TUBE	CRS	
1	SHORTING PLUG ASSEMBLY	Cu ALLOY (PIN)	YELLOW

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

FUNCTIONAL SYMBOLS: $\nabla_A = 0$, $\nabla_E = 0$, $\nabla_S = 0$

DIMENSION UNITS: INCH/MM, SCALE: 1:1

GENERAL TOLERANCES (UNLESS SPECIFIED):
 4 PLACES ±, 3 PLACES ±, 2 PLACES ±, 1 PLACE ±, 0 PLACES ±

ANGULAR TOL ± °

DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

THIRD ANGLE PROJECTION

DRAWING: B-SIZE, SERIES: 130019

EC NO: 711366, DRWN: VHANDI, CHK'D: RSTONE, APPR: BWOODMAN, INITIAL REVISION: 2013/01/15, 2013/03/01

CURRENT REV DESC: ADDED NOTES

molex

DIE BLOCK SHORTING PLUG ASSEMBLY 2 POLE, FEMALE

PRODUCT CUSTOMER DRAWING

DOCUMENT NUMBER: SD-130019-002, DOC TYPE: PSD, DOC PART: 001, REVISION: B

MATERIAL NUMBER: SEE TABLE, CUSTOMER: GENERAL MARKET, SHEET NUMBER: 1 OF 1