



### Main

|                              |                              |
|------------------------------|------------------------------|
| Range of Product             | Harmony XK                   |
| Product or Component Type    | Complete joystick controller |
| Product Specific Application | Light hoisting applications  |

### Complementary

|   |  |
|---|--|
| Device short name                           | XKB  |
| Bezel material                              | Metal  |
| Fixing collar material                      | Metal  |
| Sale per indivisible quantity               | 1  |
| Protective treatment                        | TC   |
| Ambient Air Temperature for Storage         | -40...158 °F (-40...70 °C)   |
| Ambient air temperature for operation       | -4...158 °F (-20...70 °C)  |
| Overvoltage category                        | Class I IEC 61140  |
| IP degree of protection                     | IP54 IEC 60529<br>IP20 IEC 60529   |
| Standards                                   | UL 508<br>EN/IEC 60947-5-1<br>CSA C22.2 No 14  |
| Product Certifications                      | UL<br>RRS<br>CCC<br>CSA  |
| Contact code designation                    | A300<br>Q300   |
| Operator position information               | All positions  |
| Operator profile                            | Handle with zero position mechanical interlock   |
| Notch per direction                         | 1...3 12°-20°-28° for each direction   |
| Mechanical durability                       | 1000000 cycles   |
| Vibration resistance                        | 6 gn 1...70 Hz)IEC 60068-2-6   |
| Shock resistance                            | 20 gn 11 ms) IEC 60068-2-27  |
| Connections - terminals                     | Captive screw clamp terminals, <= 2 x 1.5 mm <sup>2</sup> with cable end<br>Captive screw clamp terminals, <= 1 x 2.5 mm <sup>2</sup> without cable end<br>Captive screw clamp terminals, >= 1 x 0.5 mm <sup>2</sup> |
| Short-circuit protection                    | 10 A cartridge fuse gG EN/IEC 60947-5-1  |
| [Ith] conventional free air thermal current | 10 A EN/IEC 60947-5-1<br>10 A CSA C22.2 No 14<br>10 A UL 508   |
| [Ui] rated insulation voltage               | 500 V 3)IEC 60947-1  |

## Ordering and shipping details

|                       |                                    |
|-----------------------|------------------------------------|
| Category              | 22474 - PUSHBUTTON,CRANE JOYSTICKS |
| Discount Schedule     | I                                  |
| GTIN                  | 785901321965                       |
| Nbr. of units in pkg. | 1                                  |
| Package weight(Lbs)   | 16.00 oz (453.592 g)               |
| Returnability         | No                                 |
| Country of origin     | FR                                 |

## Packing Units

|                        |                    |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE                |
| Package 1 Height       | 6.00 in (15.24 cm) |
| Package 1 width        | 6.50 in (16.51 cm) |
| Package 1 Length       | 9.50 in (24.13 cm) |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|