

## RJI RJ45 2-port jack Cat.5 THT angled



Image is for illustration purposes only. Please refer to product description.

Part number	09 45 551 1122
Specification	RJI RJ45 2-port jack Cat.5 THT angled
HARTING eCatalogue	<a href="https://b2b.harting.com/09455511122">https://b2b.harting.com/09455511122</a>

### Identification

Category	Connectors
Series	HARTING RJ Industrial®
Element	Female
Specification	RJ45 Angled 2 ports

### Version

Termination method	Wave soldering termination
Shielding	Fully shielded, 360° shielding contact
Number of contacts	8

### Technical characteristics

Rated current	1.5 A
Rated voltage	125 V
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	10 Mbit/s 100 Mbit/s 1 Gbit/s 2.5 Gbit/s
Limiting temperature	-40 ... +85 °C
Mating cycles	≥750
Degree of protection acc. to IEC 60529	IP20



Pushing Performance  
Since 1945

## Material properties

RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

UL / CSA	UL 1977 DUXR2.E254191 CSA-C22.2 No. 182.4, No. 233-09 DUXR8.E254191
Approvals	DNV GL

## Commercial data

Packaging size	110
Net weight	11.44 g
Country of origin	Taiwan
European customs tariff number	85366990
GTIN	5713140061576
eCl@ss	27460201 PCB connector (board connector)