










RoHS Compliant



UC-302 uPCI 2xRS232 1MBaud

"SERIAL CARDS ENGINEERED TO EXCEED EXPECTATIONS"



brain boxes

Features

- 2 port RS232
- PCI 3.0
- 128 Byte Tx and 128 Byte Rx FIFOs
- Up to 921,600 Baud
- DB9 connector (9 Pin Male)
- Drivers for all popular operating systems
- Sample Programs, Test & Terminal software
- Lifetime Support
- Lifetime Warranty (registration required)

Options



uPCI 2xRS232 1MBaud

Description

Universal PCI providing two RS232 serial ports. Data transfer rates up to 921,600 baud rates and the 128 byte deep transmit and 128 byte receive FIFOS, coupled with 1Mbit/s line drivers deliver uncompromising performance on your PC.Includes drivers for all Windows 32 bit and 64 bit Operating Systems, including Windows 7.

With Brainboxes industry renowned Lifetime Warranty and Lifetime Support!

Software

Microsoft signed drivers (easy installation & robust operation) for:

- Windows 7 32 bit 64 bit Editions
- Windows Server 2008 32 bit 64 bit Editions





Windows Server 2003 32 bit 64 bit Editions

As well as: full product documentation, a thorough troubleshooting guide and terminal software. Detailed sample source code for many popular programming languages. Further OS support on next page.







ORDER Description uPCI 2xRS232 1MBaud

Code UC-302



uPCI 2xRS232 1MBaud

UC-302Full Specification

Port	Ports	2 x RS232
Pin 1 DCD RS232 Pinout (9 Pin Male)	Connector	DB9 Connector - 9 Pin Male
Pin 2 RXD Pin 1 Pin 5 Pin 3 TXD Pin 4 DTR	FIFO size	128 RX FIFO + 128 TX FIFO
Pin 5 GND Pin 6 DSR Pin 7 RTS Pin 8 CTS Pin 9 RI	Operating Distance	EIA - RS232 Standard
	Cable	No Cable; Integrated Connector
Port Settings	Baud Rate	921,600
921,600 >>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>>	Data Bits	5,6,7 or 8
	Parity	Odd, Even, None, Mark or Space
	Stop Bits	1, 1.5 or 2
	Flow Control	
	Tx/Rx Modes	Point to Point
PCI°	OS Compatibility	Microsoft Windows 7 32 bit 64 bit Editions Windows Server 2008 32 bit 64 bit Editions
		Windows Vista 32 bit 64 bit Editions Windows Server 2003 32 bit 64 bit Editions
		Windows XP 32 bit 64 bit Editions
		Microsoft Windows 2000 DOS
	BUS	PCI : Universal PCI is fully compatible with both 3.3Volt and 5Volt PC slots.
Approvals	Industry Approvals	AEO C-TPAT C-Tick Microsoft Certified Gold Partner WEEE RoHS EMC CE TAA
	Microsoft Approvals	Windows 7 32 bit 64 bit Editions Windows Server 2008 32 bit 64 bit editions Windows Vista 32 bit 64 bit editions Windows Server 2003 32 bit 64 bit editions Windows XP 32 bit 64 bit editions
General	PCB Layers	4
	Power Consumption	210mA @ 5V, 20mA @ 12V
	Weight	0.083 kg
	Size	135l x 18w x 120h mm
Box Content	Packaging	Installation CD including manual, Microsoft signed drivers & utilities
	Card	uPCI 2xRS232 1MBaud
		No Cable; Integrated Connector
Product Support	Warranty	Lifetime (online registration required)
	Support	Lifetime Web, Email and Phone Support from fully qualified, friendly
		staff who work in and alongside the Product Development Team
Additional	OEM option	Available for bulk buy OEM
Elektra O5	Made In	Manufactured in the UK by Brainboxes Winner 2005 European Electronics Industry Awards "Manufacturer of the Year"
WINNER Manufacturer of the Year Made in the UK	Customisable	Brainboxes operate a "Perfect Fit Custom Design" policy for volume users. More Info: sales@brainboxes.com

Other PCI Cards: 1xRS232 | 2xRS232 | 4xRS232 | 8xRS232 | 1xRS422/485 | 2xRS422/485 | 4xRS422/485 Other Brainboxes Ranges: PCI Express | Bluetooth Serial Adapter | Ethernet to Serial Adapter | PCMCIA Serial Card | ExpressCard Serial Adapter | USB to Serial