1600236-4 - ACTIVE

### **MULTI-BEAM**

TE Internal #: 1600236-4 Rectangular Power Connectors, Header, Plug, Cable-to-Panel, 26 Position, 2.54 mm [.1 in] Centerline, Printed Circuit Board, UL 94V-0 View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Header

Connector & Housing Type: Plug

Connector System: Cable-to-Panel

Number of Positions: 26

Centerline (Pitch): 2.54 mm [.1 in]

# Features

# Product Type Features

Rectangular Power Connector Type	Header
Connector & Housing Type	Plug
Connector System	Cable-to-Panel
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	26
Number of Power Positions	2
Number of Signal Positions	24
Number of Rows	4
Electrical Characteristics	
Operating Voltage	60 VDC
Contact Features	
Power Contact Base Material	Tin

## 1600236-4

Rectangular Power Connectors, Header, Plug, Cable-to-Panel, 26 Position, 2.54 mm [. 1 in] Centerline, Printed Circuit Board, UL 94V-0



Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	45 A
Contact Retention Within Housing	Without
Contact Type	Blade, Pin
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
PCB Mount Retention	Without
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	2.54 mm[.1 in]
Housing Color	Black
Housing Material	Thermoplastic
Dimensions	
Row-to-Row Spacing	2.54 mm[.1 in]

# Usage Conditions

China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
	•
EU ELV Directive 2000/53/EC	Compliant
EU RoHS Directive 2011/65/EU	Compliant
Product Compliance For compliance documentation, visit the product page on TE.com>	
Packaging Method	Box
Packaging Features	
Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-0
Industry Standards	
Circuit Application	Power & Signal
Operation/Application	
Operating Temperature Range	-20 – 105 °C[-4 – 221 °F]

**C** For support call+1 800 522 6752

## 1600236-4

Rectangular Power Connectors, Header, Plug, Cable-to-Panel, 26 Position, 2.54 mm [. 1 in] Centerline, Printed Circuit Board, UL 94V-0



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**



# Customers Also Bought



# Documents

Product Drawings PAN MT PLUG, MBXL, 1P+24S+1P English

**C** For support call+1 800 522 6752

### 1600236-4

Rectangular Power Connectors, Header, Plug, Cable-to-Panel, 26 Position, 2.54 mm [. 1 in] Centerline, Printed Circuit Board, UL 94V-0



# **CAD** Files

3D PDF

3D **Customer View Model** ENG\_CVM\_CVM\_1600236-4\_D.2d\_dxf.zip English **Customer View Model** ENG\_CVM\_CVM\_1600236-4\_D.3d\_igs.zip

English

Customer View Model ENG\_CVM\_CVM\_1600236-4\_D.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

POWER\_CONNECTORS\_CATALOG\_SEC01\_BOARD\_TO\_BOARD

English

MULTI-BEAM XL Cable Plug Assemblies Datasheet 6-1773442-7

English

**Product Specifications Application Specification** 

English

Agency Approvals Agency Approval Document

English