

**-** .100 [2.54] (3)

.450 [11.43]

P.C.B. RECOMMENDED HOLE LAYOUT SEEN FROM COMPONENT SIDE

ALL CENTERLINE DIMENSIONS ARE BASIC.

.050 [1.27] (7)

PIN #1-

ø.035 [0.89] ±.003 [0.08] (8)

ф Ø.006 [0.15]

ø .128 [3.25] .125 [3.18]

**♦** Ø.006 [0.15]

.050 [1.27]—

## NOTES:

- 1. CONNECTOR MATERIALS: HOUSING: THERMOPLASTIC UL94 V-0 CONTACTS/SHIELD: COPPER ALLOY SHIELD PLATING: NICKEL OR TIN CONTACT PLATING: SELECTIVE GOLD IN CONTACT AREA SEE CHART FOR PART NUMBER
- 2. FOR PRODUCT SPECIFICATIONS SEE PR022-01.
- 3. DIMENSIONS AND TOLERANCES COMPLY WITH TIA-1096 STANDARD.

30 MICRO-INCHES [0.76um]	SS-6488-NF-RMK
CONTACT PLATING IN MATING AREA	PART NUMBER



THIRD ANGLE PROJECTION DO NOT SCALE DRAWING

DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE

DIMENSIONS: INCHES [METRIC] UNLESS OTHERWISE SPECIFIED

TOLERANCES ARE ±.005 [0.13]
ANGLES ARE ± 1'

1 OF

SHEET NO.

a bel group

11118 Susquehanna Trail South Glen Rock, PA 17327-9199 (717) 235-7512

http://www.stewartconnector.com

В

Α

EIGHT CONTACT, EIGHT POSITION, UNSHIELDED JACK NON-FLANGE, RMK KEYING OPTION

THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREON ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTEI CONSENT OF STEWART CONNECTOR. ONE OR MORE U.S. PATEN MAY APPLY TO THIS PRODUCT. FOR DETAILS, PLEASE

VISIT: HTTP://BELFUSE.COM/STEWART/STEWART\_PATENTS

)N F	DRN BY:	SAR	DATE 2-	20-	03
EN ENTS	APPD BY:	RGC	DATE 2-	25-	03
5/	DWG NO.	CT640068		REV.	C7

AutoCAD

—.450 [11.43]—<del>-</del>

.415 [10.54]-

[20.70] MAX.