

# Automotive grade High-speed protection against ESD



## Extra low capacitance, automotive-grade ESD protection for HDMI, USB 3.0 APIX, LVDS and Ethernet communication buses

Infotainment systems such as in-seat multimedia screens or central information displays require high-speed communication interfaces made of surge sensitive ICs. Due to automotive reliability standards, the use of AEC-Q101 compliant protection is mandatory.

ST's automotive grade HSP device meets high-speed interface needs in terms of robustness (IEC 61000-4-2 compliant), transparency (high bandwidth and low capacitance) and design constraints. Indeed, our small package and flow-through pinout allow high-density PCBs

and improve signal integrity. The HSP061 in particular is AEC-Q101 compliant and compatible with all communication ports. This makes it the most versatile and easy-to-design product on the market.

### KEY FEATURES

- AEC-Q101 compliant
- 1-, 2-, 4-line ESD protection
- Capacitance (I/O) down to 0.3 pF
- Best-in-class bandwidth: up to 10 GHz
- Compliant with
  - 8 kV ESD (IEC 61000-4-2)
  - ISO 7637 3a and 3b
- Ultra small package

### KEY BENEFITS

- Enables high-density PCB due to small package
- Simplifies design with :
  - Transparency: large bandwidth
  - Flow-through routing for improved signal integrity

### KEY APPLICATIONS







- High-speed interfaces (LVDS, HDMI, Ethernet, USB 3.0 APIX)
- Infotainment (including in-seat multimedia screens, central displays, cameras)

# ELECTRICAL PARAMETERS

Product	Number of lines	V <sub>BR</sub> min	Capacitance (I/O/I/O) typ	Bandwidth
HSP061-4M10Y	4	6 V	0.3 pF	8.7 GHz
HSP061-2P6Y	2	6 V	0.3 pF	6 GHz
ESDAXLC6-1BT2Y*	1	6 V	0.4 pF	10 GHz


Note : \*Available in March 2014

## PACKAGE DRAWING

HSP061-4M10Y		HSP061-2P6Y		ESDAXLC6-1BT2Y	
<p>μQFN-10L 2.5x1x0.5 mm 500 μm pitch</p> 		<p>SOT666 1.6x1.6x0.6 mm 500 μm pitch</p> 		<p>SOD882 Thin 1x0.6x0.4 mm 600 μm pitch</p> 	


### HSP061-4M10Y

#### HDMI (3.4 Gbit/s) eye diagram




### HSP061-2P6Y

#### HDMI (3.4 Gbit/s) eye diagram




### HSP061-4M10Y

#### Layout recommendation



### ESDAXLC6-1BT2Y

#### Attenuation versus frequency



© STMicroelectronics - February 2014 - Printed in United Kingdom - All rights reserved  
The STMicroelectronics corporate logo is a registered trademark of the STMicroelectronics group of companies  
All other names are the property of their respective owners

