


REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
A	INITIAL RELEASE	12/08/08	D.N.



NOTES:



MATERIALS:

1. INSULATOR = VIRGIN WHITE TEFLON PER ASTM D1710, GRADE 1, TYPE I, CLASS "B".
2. LOCKWASHER = PHOSPHOR BRONZE PER ASTM B139, COPPER ALLOY C53400, TEMPER H04.
3. ALL OTHER METAL PARTS = BRASS PER ASTM B16, ALLOY C36000, TEMPER H02.

FINISHES:

1. CONTACT = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 1, GRADE C, OVER .00010 TO .00020 STRESS FREE SULFAMATE NICKEL PER QQ-N-290.
2. ALL OTHER METAL PARTS = GOLD PLATE PER MIL-G-45204, TYPE II, CLASS 0, GRADE C, OVER .00010 TO .00020 COPPER STRIKE PER MIL-C-14550.

Property of Radiall Incorporated
 This document cannot be reproduced or
 communicated to a third party without prior
 written permission of RADIALL Incorporated.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ON	DWN:	DATE	 APPLIED ENGINEERING PRODUCTS 104 John W. Murphy Dr. New Haven, CT 06513
	D.N.	12/08/08	
DECIMAL	ANGLE	CHKD:	SMC STRAIGHT MALE JACK BULKHEAD MOUNT P.C.B. RECEPTACLE
		A.D.M.	
		APVD:	DATE
		J.M.	12/08/08
REFERENCE:	MATERIALS & FINISHES:		SIZE
ORIGINATOR: D.N. DATE: 12/08/08	SEE NOTES		A
			FSCM NO.
			19505
			DWG. NO.
			1109-1511-000
			REV
			A
			SCALE
			6:1
			THIRD ANGLE PROJECTION
			
			SHEET 1 OF 1

1109-1511-000