

THIS IS A CONTROLLED DOCUMENT.

REV ITEM 37 PER R2416 4/28/83 3/78 T PER ECN A-26190 JR CE 7-31-90

AMP 1281-1 (6/78)

APPLICATOR PARTS LIST

MINIATURE QUICK CHANGE APPLICATOR
END FEED

AMP INCORPORATED
HARRISBURG, PENNA.

TYPE CODE
 PROD
 IN DIR
 W.O.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.	CRIMPING DATA			TERMINALS
1	WIRE CRIMPER 453828-2	1	690105-3	43	WASHER-LAMINATED	1	690125-1	TO APPLY TERMINAL			60755
2	SPACER - INSULATION	1	1-690407-7	44	RAM	1	690550-1	SPEC 114-2079			62435
3	INSULATION CRIMPER	1	690406-2	45	PLUG-NYLON	1	690191-1	PAD LETTER	CRIMP HEIGHT	WIRE SIZE	63848
4	PIN - CRIMPER	1	238009-1	46	BLOCK-INS. ADJ.	1	690402-1	A	.057	1 #16	
5	SHEAR BLADE SPACER			47	SCREW-SHOULDER 22353-8	1	690227-1	B	.049	1 #18	
6	HOLD DOWN			48	CAM	1	238015-1	C	.045	1 #20	
7	SHEAR BLADE	1	690612-1	49	CRIMPER BOLT 7-21002-9	1	690323-1	D	NOT	USED	
8	ANVIL	1	240694-2	50	SCREW, DRIVE #2x.19LG	2	21017-2	CRIMP	SIZE	TYPE	FEED
9	FRONT SHEAR PLATE	1	690552-1	51	PLATE IDENTIFICATION	1	461264-1	WIRE	.090	F	
10	SHEAR PLATE SPACER 469488-1	1	690611-1	52	LEVER-TERMINAL	1	240634-1	INSUL.	.140	F	.525
11	REAR SHEAR PLATE	1	690631-1	53	FEED FINGER	1	690532-1	INSULATION RANGE		WIRE RANGE	
12	HOLD DOWN SPRING			54	FEED FINGER SPRING 621499-1	1	240635-1	.090 - .130		20 - 16	
13	SPRING SPACER			55	FEED FINGER PIN	1	240624-1	EXPLODED VIEW		SET UP GAGE	
14	HOLD DOWN SPACER			56	Feed Arm	1	690529-1	A-6090		679108-1	
15				57				REMARKS:			
16	SPRING - FEED RETURN 3-22288-0	1	690127-1	58	HOUSING	1	690553-1	AMPOMATOR			
17	ANCHOR - SPRING	1	238008-1	59	CAP	1	240621-1				
18	FRONT - STRIP GUIDE	1	690531-1	60	WEAR PLATE	1	690648-1				
19	REAR - STRIP GUIDE	1	690530-1	61	ROD-FEED	1	690649-1				
20	DRAG - STOCK	1	240696-2	62	ROLLER-CAM	1	240658-1				
21	DRAG LEVER	1	240636-1	63	PIN-CAM ROLLER	1	240659-1				
22	DRAG SPRING 7-22282-5	1	240810-1	64	SCREW-ADJ.	1	240632-1				
23	PLATE - STRIP HOLD			65	BLOCK-PIVOT	1	240629-1				
24	STRIP GUIDE PLATE	1	690528-1	66	LEVER-INTERMEDIATE	1	240630-1				
25	BASE BLOCK	1	690555-1	67	BUSHING	1	240633-1				
26	BASE PLATE	1	690554-1	68	SHAFT-PIVOT	1	240626-1				
27	STRIPPER	1	690634-1	69	PLATE ADJ.	1	240628-1				
28	RETAINING PLATE			70	HEX NUT 22594-8	1	376926				
29	SHOULDER SCREW			71	SPACER	1	690517-1				
30	ANCHOR SPACER	1	690453-1	72	Spring Assist	2	690603-1				
31	SPACER - BASE BLOCK			73	Terminal Lift	1	690636-1				
32	Shear Blade-Side	1	690549-9	74	Bushing Term. Lift	1	690644-1				
33	Shear Blade-Side	1	690551-1	75	Spring Term. Lift	1	690645-1				
34	Strip Guide Spacer	1	690610-1	76							
35	POST-RAM	1	690212-1	77	GUARD, CHIP	1	469487-1				
36	SPRING WASHER 22480-5	1	690133-1	78							
37	DISC-WIRE 3-690141-2	1	6-690141-0	79	GUARD, ASSY	REF	453750-5				
38	DISC-INSULATION	1	690142-1	REV. REVISION RECORD		DATE	BY	ECN	THIS APPLICATOR IS TO BE USED ON		
39	SPRING-COMPRESSION	2	690170-1	T1	0150-6205-95	6-95	PM		MACH. SERIAL NO.		DIST.
40	BALL STEEL 23241-6	2	690169-1	T2	0150-1144-04	9-04	ML		MACH. PARTS LIST		
41	DISC SPACER			C. REV. PER 1.5.1		4/20/01	PM	106	APPL. SERIAL NO.	DATE SHIPPED	DESIGNED
42	WASHER RAM	1	690124-1						CUSTOMER NAME AND ADDRESS		CHK'D.
								APPLICATOR NUMBER	REV. T2	686262-4	APP'D.
										SHEET	1 OF 1

RELEASED FOR PUBLICATION
 BY AMP INCORPORATED. ALL RIGHTS RESERVED.
 COPYRIGHT 2000

00779

CUSTOMER AND ASSEMBLY DRAWING

RESTRICTED TO