

In case of consideration for using Automotive equipment / device which demand high reliability, kindly contact our sales window correspondents.

<b>APPLICABLE STANDARD</b>		ANSI/TIA/EIA-568-B.2.10 CAT6a	
OPERATING TEMPERATURE RANGE		<input type="checkbox"/> 1 $-25^{\circ}\text{C}$ TO $60^{\circ}\text{C}$	STORAGE TEMPERATURE RANGE
RATING			$-25^{\circ}\text{C}$ TO $60^{\circ}\text{C}$
VOLTAGE	125 V AC	OPERATING HUMIDITY RANGE	95 % MAX
CURRENT	1 A	APPLICABLE CABLE	-
<b>SPECIFICATIONS</b>			
ITEM	TEST METHOD	REQUIREMENTS	QT
<b>CONSTRUCTION</b>			AT
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X
MARKING	CONFIRMED VISUALLY.		X

  

<input type="checkbox"/> 1	① THE OPERATION TEMPERATURE INCLUDES THE TEMPERATURE RISE BY CURRENT CARRYING. ② TEMPERATURE RANGE FOR A CONNECTOR UNMATED. ③ USE UNDER THE CONDITION RECOMMENDED BY A CABLE MANUFACTURE.		
REMARK	DESIGNED	CHECKED	DATE
Unless otherwise specified, refer to JIS C 5402. Note QT:Qualification Test AT:Assurance Test X:Applicable Test	APPROVED	YH. EMAMI	09.06.02
	CHECKED	YH. EMAMI	09.06.02
	DESIGNED	MT. ITANO	09.06.02
	DRAWN	MT. ITANO	09.06.02

  

<b>HRS</b>	SPECIFICATION SHEET	PART NO.	TM31P-TM-88P (02)
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL222-4626-7-02
		DRAWING NO.	ELC4-126868-02
			1/1