



Resistance to soldering heat: acc to IEC 60 068-2-20 Part 2, Test Tb, method 1B 350°C-3,5s.
Solderability: acc to IEC 60 068-2-20 Part 2, Test Ta, method 1, 235°C-2 sec.

| | | | | | |
|---|-----------------|---|---------------|---|----------------------|
| UN-D1041 | | TOLERANCES UNLESS OTHERWISE STATED TOLERANTIES TENZU ANDERS VERMELD | | | |
| | | DIMENSION MAAT | ANGLE HOEK | | |
| GENERAL ROUGHNESS ALGEMENE RUWHEID | UNIT EENH. | MATERIAL MATERIAAL | | ASSEMBLY NO. SAMENSTELLINGSNR. | QUANT AANTAL |
| ✓ | mm | Rynite FR530 (PET) ,glass-reinforced (color black) UL file number: E41938 - UL94V-0. Pin material: Copper-plated steel wire, Sn plated. | | PATTERN NO./MODELNR. | |
| SCALE SCHAAL | PROJ. EUROP. | TREATMENT BEHANDELING | | ORDER NO./ORDERNR | QUANT AANTAL |
| | | | | | |
| CLASSNO. | | CPV-PQ20/16-1S-14P-Z | | 4335 060 26711 | 07-09-03 07-09-20 |
| NAME NAAM | A.Wojtasz | SUPERS. VERV. | | SH BL. 110 - 001 | 010 |
| MPA | CHECK CONTR. | DAT. | 07-09-03 | Property of Eigendom van © FERROXCUBE 2007 | |
| | | | | | A3 |