NSYCR20WU2

ClimaSys PTC heating resistance 20W, 110-250V



Main

Man	
Range	ClimaSys
Product name	ClimaSys CR
Product or Component Type	Resistance heater
Power range	20 W
Input voltage	110250 V AC 50/60 Hz
Electrical connection	Cable 2 x 0.75 mm² 11.81 in (300 mm)

Complementary

Operating position	Vertical	
Ambient Air Temperature for Operation	-40158 °F (-4070 °C)	
IP Degree of Protection	IP20	
Product Certifications	UL VDE	
Material	Body extruded aluminium	
Height	External 3.35 in (85 mm)	
Width	External 0.98 in (25 mm)	
Depth	External 2.24 in (57 mm)	
Condition of use	Air sealed enclosure Heaters must be installed with a thermal controller Electrical protection is needed	
Fixing Mode	By clips	
Mounting Support	35 mm DIN rail	

Ordering and shipping details

ordering and emphing detaile	
Category	80036-ENCLOSURE SYSTEMS ACCESSORIES
Discount Schedule	ES1
GTIN	3606480152139
Nbr. of units in pkg.	1
Package weight(Lbs)	5.71 oz (162.0 g)
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	2.76 in (7 cm)	
Package 1 width	3.15 in (8 cm)	
Package 1 Length	4.33 in (11 cm)	
Unit Type of Package 2	P12	
Number of Units in Package 2	300	
Package 2 Weight	132.60 lb(US) (60.145 kg)	
Package 2 Height	17.72 in (45 cm)	
Package 2 width	31.50 in (80 cm)	
Package 2 Length	47.24 in (120 cm)	

Unit Type of Package 3	S04	
Number of Units in Package 3	75	
Package 3 Weight	27.64 lb(US) (12.536 kg)	
Package 3 Height	11.81 in (30 cm)	
Package 3 width	15.75 in (40 cm)	
Package 3 Length	23.62 in (60 cm)	

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------