


DESCRIPTION: 25 POS MICRO-D FEMALE (ASSEMBLED) TO BLUNT CUT

THUMBSCREWS: NICKEL PLATED STEEL - UNC #2-56 THREAD



- 1. P1: NORCOMP MICRO D 25S, ASSEMBLED HOOD W/THUMBSCREWS
- 2. P2. BLUNT CUT END
- 3. WIRE: 28AWG [7X36] x25C +ALUMINUM FOIL + BRAID 65%, UL2464, COLOR BLACK
- 4. PINOUT:

P1	P2
1	BLACK
2	BROWN
3	RED
4	ORANGE
5	YELLOW
6	GREEN
7	BLUE
8	VIOLET
9	GRAY
10	WHITE
11	PINK
12	LIGHT GREEN
13	BLACK WHITE
14	BROWN WHITE
15	RED WHITE
16	ORANGE WHITE
17	GREEN WHITE
18	BLUE WHITE
19	VIOLET WHITE
20	RED BLACK
21	ORANGE BLACK
22	YELLOW BLACK
23	GREEN BLACK
24	GRAY BLACK
25	PINK BLACK
SHELL	SHIELD

P/N	L ± T
CCA-025-I18R152	18±0.590in
CCA-025-I36R152	36±0.787in
CCA-025-I72R152	72±0.984in
CCA-025-M.5R152	500±15mm
CCA-025-M01R152	1000±20mm
CCA-025-M02R152	2000±25mm
CCA-025-F08R152	8±0.17ft
CCA-025-F10R152	10±0.17ft
CCA-025-F60R152	60±0.5ft

NOTE:

**NOT DESIGNED TO MATE WITH NORCOMP 580-M // 581-M SERIES CONNECTORS. IF ANY QUESTIONS PLEASE CONTACT ENG@NORCOMP.NET

RoHS COMPLIANT

PACKAGED: 1 PER BAG

DO NOT SCALE FROM DRAWING

	THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.	DRAWN: P. JENKINS		SCALE: NTS	SHEET OF 1 1	REV 6
		DATE: 01/18/2012		DWG NO. CCA-025-YYYYR152		