

1388LA Multi-Conductor - Media, Automation and Lighting Control

For more Information
please call

1-800-Belden1



General Description:

Lighting & Automation Cable, Rated-CL3, 2-16 AWG bare copper conductors unshielded, PVC insulation (power), 1-18 AWG bare copper conductor unshielded, PVC insulation and 1 (data) triad 22 AWG stranded bare copper, PVC insulation, Beldfoil® shield w drain, PVC jacket.

Physical Characteristics (Overall)

Conductor

AWG:

| # Conductors | # Triads | AWG | Stranding | Conductor Material |
|--------------|----------|-----|-----------|--------------------|
| | 1 | 22 | 7x30 | BC - Bare Copper |
| 1 | | 18 | 19x30 | BC - Bare Copper |
| 2 | | 16 | 26x30 | BC - Bare Copper |

Total Number of Conductors: 6

Insulation

Insulation Material:

| Insulation Material | AWG |
|--------------------------|-----|
| PE - Polyethylene | 22 |
| PVC - Polyvinyl Chloride | 18 |
| PVC - Polyvinyl Chloride | 16 |

Inner Shield

Inner Shield Material:

| Layer # | Inner Shield Trade Name | Type | Inner Shield Material | Coverage (%) |
|---------|-------------------------|------|------------------------------|--------------|
| 22 AWG | Beldfoil® | Tape | Aluminum Foil-Polyester Tape | 100.000 |

Inner Shield Drain Wire AWG:

| AWG |
|-----|
| 24 |

Inner Shield Drain Wire Stranding: 7x32

Inner Shield Drain Wire Conductor Material: TC - Tinned Copper

Outer Shield

Outer Shield Material:

| Outer Shield Material |
|-----------------------|
| Unshielded |

Outer Jacket

Outer Jacket Material:

| Outer Jacket Material |
|--------------------------|
| PVC - Polyvinyl Chloride |

Outer Jacket Ripcord: No

Overall Cable

Overall Nominal Diameter: 8.687 mm

Pair

Pair Color Code Chart:

| Number | Color |
|--------|------------------------------|
| 1 | Purple, White & Gray (22AWG) |

1388LA Multi-Conductor - Media, Automation and Lighting Control

| | |
|---|----------------------|
| 2 | Red & Black (16AWG) |
| 3 | Yellow/Green (18AWG) |

Mechanical Characteristics (Overall)

| | |
|-----------------------------------|----------------|
| Operating Temperature Range: | -20°C To +60°C |
| Bulk Cable Weight: | 98.221 Kg/Km |
| Max. Recommended Pulling Tension: | 587.162 N |
| Min. Bend Radius/Minor Axis: | 88.900 mm |

Applicable Specifications and Agency Compliance (Overall)

Applicable Standards & Environmental Programs

| | |
|------------------------------------|---------|
| NEC/(UL) Specification: | CL3, CM |
| CEC/C(UL) Specification: | CM |
| EU Directive 2011/65/EU (ROHS II): | Yes |
| EU CE Mark: | Yes |
| EU Directive 2000/53/EC (ELV): | Yes |
| EU Directive 2002/95/EC (RoHS): | Yes |
| EU Directive 2002/96/EC (WEEE): | Yes |
| EU Directive 2003/11/EC (BFR): | Yes |
| CA Prop 65 (CJ for Wire & Cable): | Yes |
| MII Order #39 (China RoHS): | Yes |

Flame Test

| | |
|----------------|----------------------|
| UL Flame Test: | UL1581 Vertical Tray |
|----------------|----------------------|

Suitability

| | |
|-----------------------|-----|
| Suitability - Indoor: | Yes |
|-----------------------|-----|

Plenum/Non-Plenum

| | |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

Electrical Characteristics (Overall)

Nom. Conductor DC Resistance:

| Description | DCR @ 20°C (Ohm/km) |
|-------------|---------------------|
| 22AWG | 52.824 |
| 18AWG | 21.327 |
| 16AWG | 13.780 |

Max. Operating Voltage - UL:

| Voltage |
|-----------|
| 300 V RMS |

Max. Recommended Current:

| Description | Current |
|-------------|-------------------------------|
| 22AWG | 3.3 Amps per conductor @ 25°C |
| 18AWG | 6.3 Amps per conductor @ 25°C |
| 16AWG | 7.9 Amps per conductor @ 25°C |

Notes (Overall)

Notes: Sequential footage marking every two feet.

Put Ups and Colors:

| Item # | Putup | Ship Weight | Color | Notes | Item Desc |
|---------------|--------|-------------|-------|-------|--------------------------------|
| 1388LA 009250 | 250 FT | 18.000 LB | WHITE | | 2#16,1#18,1 FS TRIAD #22 FRPVC |

1388LA Multi-Conductor - Media, Automation and Lighting Control

Revision Number: 1 Revision Date: 03-13-2013

© 2019 Belden, Inc
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 2014/35/EU).