



SS Stainless Steel

Metric table

Dimensions in: millimeters - inches

d ₁	d ₂ Thread	Length l										d ₃	h ₁	h ₂
		ZP												
22 .87	M 4	10 .39	25 .98	-	-	-	-	-	-	-	-	15 .59	14 .55	6 .24
22 .87	M 5	10 .39	15 .59	-	-	-	-	-	10 .39	-	-	15 .59	14 .55	6 .24
22 .87	M 6	10 .39	15 .59	20 .79	25 .98	30 1.18	35 1.38	40 1.57	-	-	-	15 .59	14 .55	6 .24
24 .94	M 4	10 .39	25 .98	-	-	-	-	-	-	-	-	15 .59	14 .55	6 .24
24 .94	M 5	10 .39	-	-	-	-	-	-	-	-	-	15 .59	14 .55	6 .24
24 .94	M 6	10 .39	15 .59	25 .98	-	-	-	-	-	-	-	15 .59	14 .55	6 .24
26 1.02	M 5	10 .39	15 .59	25 .98	-	-	-	-	-	-	-	16 .63	15 .59	6 .24
26 1.02	M 6	10 .39	15 .59	20 .79	25 .98	40 1.57	-	-	20 .79	30 1.18	-	16 .63	15 .59	6 .24
26 1.02	M 8	25 .98	-	-	-	-	-	-	-	-	-	16 .63	15 .59	6 .24

Specification

- Nylon plastic
 - Glass filled
 - Temperature resistant up to 230 °F (110 °C)
 - Black, matte finish

- **ZP**
 - Threaded stud
 - Steel, zinc plated

- **ZPX**
 - Threaded stud
 - Stainless steel, molded-in
 - European Standard No. 1.4301 (AISI 304)

- RoHS compliant

On request

- For certain minimum quantities, custom colors or special studs

Information

More shock proof than their phenolic counterpart, these ZP and ZPX knurled screws provide excellent slip-free clamping and fastening.

How to order (Steel threaded stud) ¹ ² ³ ZP-24-M5-10	1	Handle diameter d ₁
	2	Thread d ₂
	3	Length l

How to order (Stainless steel threaded stud) ¹ ² ³ ZPX-26-M6-20	1	Handle diameter d ₁
	2	Thread d ₂
	3	Length l