

box terminal 4 units accessory for: 3VA5 250



Model	
product brand name	SETRON
product designation	accessories
Accessories	Box terminal
General technical data	
designation / of the terminal	TS1.2
Connections according IEC	
connectable conductor cross-section	6 mm ² 120 mm ²
<ul style="list-style-type: none"> • for copper cable / stranded / minimum • for copper cable / stranded / maximum 	
stripped length	19 mm
tightening torque / when using copper cables	6 - 16 mm ² : 6 Nm 6 - 25 mm ² : 6Nm 35 - 120 mm ² : 10 Nm 10 - 25 mm ² : 6 Nm 35 - 95 mm ² : 10Nm
<ul style="list-style-type: none"> • solid • stranded • finely stranded 	
Connections according UL	
stripped length	0.75 in
connectable conductor cross-section	10 AWG 10 AWG 10 AWG 3/0 AWG 10 AWG 3/0 AWG
<ul style="list-style-type: none"> • for copper cable / solid / minimum • for copper cable / solid / maximum • for copper cable / stranded / minimum • for copper cable / stranded / maximum • for copper cable / finely stranded / minimum • for copper cable / finely stranded / maximum 	
tightening torque / when using copper cables	10 AWG: 105 lb-in 10 - 4 AWG: 105 lb-in 3 - 3/0 AWG: 140 lb-in 10 - 4 AWG: 105 lb-in 3 - 3/0 AWG: 140 lb-in
<ul style="list-style-type: none"> • solid • stranded • finely stranded 	
Further information	
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs	
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9234-0JA11	
Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/3VA9234-0JA11	
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...) http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9234-0JA11	
CAX-Online-Generator http://www.siemens.com/cax	
Tender specifications http://www.siemens.com/specifications	

last modified:

7/5/2022 