

Data sheet | Item number: 763-1108

8-channel digital input; 24 VDC; High-Speed


www.wago.com/763-1108



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

This three-part digital input module is a 2-wire device featuring eight channels in a width of just 12 mm (0.47 inch).

The module consists of a base module, an electronic module and a pluggable connector.

It receives binary control signals from digital field devices (e.g., sensors, encoders, switches or proximity sensors) with a short-circuit-proof sensor supply.

The module features Push-in CAGE CLAMP® connections, enabling solid conductors to be connected by simply pushing them in.

A green LED indicates the signal state of each channel.

Field and system levels are electrically isolated.

Data

Technical data

Device-specific

Synchronization mode: time-synchronized, freewheeling

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Number of digital inputs	8
Total number of channels (module)	8
Signal type	Voltage
Signal type (voltage)	24 VDC
Sensor connection	8 x (2-wire)
Input characteristic	High-side switching
Input characteristic	Type 3, per IEC 61131-2
Input filter	1 μ s
Input current at specific input voltage	2.4 mA at 24 V
Delay time T _{on} from 0 to 1	3 μ s
Delay time T _{off} from 1 to 0	6 μ s
Data width	8-bit channel status
Supply voltage (field)	24 VSELV DC (-25 ... +30 %); UF
Current consumption, field supply (module with no external load)	14 mA
Power loss P _I	0.9 W
Isolation, Field/System	min. 1000 VDC (1 min); per EN/UL 61010-2-201
Dielectric strength	Up to \pm 35 V, at the digital input
Number of incoming power jumper contacts	2
Number of outgoing power jumper contacts	2
Current carrying capacity (power jumper contacts)	12 A
Marking	CI I, Div. 2, Group A, B, C, D, T4

Connection data

Connection type 1	Inputs/outputs
Solid conductor	0.25 ... 1.5 mm ² / 22 ... 16 AWG
Fine-stranded conductor	0.25 ... 1.5 mm ² / 22 ... 16 AWG
Strip length	8 ... 9 mm / 0.31 ... 0.35 inches
Note (conductor cross-section)	Insulated ferrule: 0.75 mm ² (max.)

Physical data

Width	12 mm / 0.472 inches
Height	105 mm / 4.134 inches
Depth	75 mm / 2.953 inches

Mechanical Data

Mounting type	DIN-35 rail
---------------	-------------

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Material Data

Fire load	0.062 MJ
Weight	70 g
Conformity marking	CE

Environmental requirements

Ambient temperature (operation)	-25 ... +60 °C (horizontal, typical control cabinet installation; -25 ... +50 °C, other mounting positions)
Ambient temperature (storage)	-40 ... +85 °C
Protection type	IP20
Pollution degree	2
Operating altitude	without temperature derating: 0 ... 2000 m; with temperature derating: 2000 ... 3000 m (0.5 K/100 m)
Mounting position	horizontal, typical for control cabinets (nominal mounting position); horizontal (floor mounting position); standing (vertical at bottom)
Relative humidity (without condensation)	95 %
EMC immunity to interference	per EN 61000-6-1, -2
EMC emission of interference	per EN 61000-6-3, -4

Commercial data

Recupel Type	
PU (SPU)	1 pcs
Country of origin	DE
GTIN	4055143975841
Customs tariff number	8538909990

Environmental Product Compliance

CAS-No.	1303-86-2 1317-36-8 693-98-1 7439-92-1 79-94-7
REACH Candidate List Substance	2-methylimidazole Diboron trioxide Lead Lead monoxide Perfluorobutane sulfonic acid (PFBS) and its salts Tetrabromobisphenol A (TBBPA)
RoHS Compliance Status	Compliant, With Exemption

Subject to changes. Please also observe the further product documentation!



RoHS Exemption	7(a) 7(c)-I 7(c)-II
SCIP notification number (Bulgaria)	be4a6648-3cc8-406e-835d-85f2d7156fc8
SCIP notification number (Czech Republic)	d68909c4-f4c1-4b80-97c1-9ce4285accf7

Approvals / Certificates

General approvals

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc. (ORDINARY LOCATIONS)	UL 61010-2-201	E175199

Declarations of conformity and manufacturer's declarations

Logo	Approval	Additional Approval Text	Certificate name
	EU-Declaration of Conformity WAGO GmbH & Co. KG	-	-

Approvals for marine applications

Logo	Approval	Additional Approval Text	Certificate name
	BV Bureau Veritas S.A.	Rules for class. of Steel Ships	66432/A0
	DNV DNV Germany GmbH	DNV-CG-0339, Aug. 2021	TAA000031M

Approvals for hazardous areas

Logo	Approval	Additional Approval Text	Certificate name
	UL Underwriters Laboratories Inc. (HAZARDOUS LOCATIONS)	UL 121201	E198726

Installation Notes

Product family

WAGO I/O System Advanced
[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.