1-2199230-6 - ACTIVE

M.2 NGFF

TE Internal #: 1-2199230-6 M.2 Connectors, Height .165 in [4.2 mm], Connector & Keying Code M, Gold, Power, -40 – 176 °F [-40 – 80 °C], M.2 NGFF

View on TE.com >

Connectors > PCB Connectors > Card Edge Connectors > M.2 Connectors > M.2 Connectors



Connector Height: 4.2 mm [.165 in] Connector & Keying Code: M

Contact Mating Area Plating Material: Gold

Connector System: Board-to-Board

Number of Positions: **67**

All M.2 Connectors (29)



Features

Product Type Features

Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Rows	2
PCB Mount Orientation	Right Angle
Number of Positions	67
Electrical Characteristics	
Operating Voltage	50 VAC
Body Features	
Primary Product Color	Black
Connector & Keying Code	M
Contact Features	
	30 µin

C For support call+1 800 522 6752

M.2 Connectors, Height .165 in [4.2 mm], Connector & Keying Code M, Gold, Power, -40 – 176 °F [-40 – 80 °C], M.2 NGFF



PCB Contact Termination Area Plating Material Finish	Matte
PCB Contact Termination Area Plating Material	Gold Flash, Tin
Contact Base Material	Copper Alloy
Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	.5 A
Termination Features	
Termination Method to Printed Circuit Board	Surface Mount
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	High Temperature Thermoplastic
Centerline (Pitch)	.5 mm[.02 in]
Dimensions	
Connector Length	21.9 mm[.862 in]
Connector Width	8.7 mm[.343 in]
Connector Height	4.2 mm[.165 in]
Usage Conditions	
Operating Temperature Range	-40 – 80 °C[-40 – 176 °F]
Operation/Application	
Circuit Application	Power
Packaging Features	
Packaging Method	Tape & Reel
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC

M.2 Connectors, Height .165 in [4.2 mm], Connector & Keying Code M, Gold, Power, -40 – 176 °F [-40 – 80 °C], M.2 NGFF



Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Reflow solder capable to 260°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts






Also in the Series | M.2 NGFF



Customers Also Bought

M.2 Connectors, Height .165 in [4.2 mm], Connector & Keying Code M, Gold, Power, -40 – 176 °F [-40 – 80 °C], M.2 NGFF





TE Part #2397013-4 #4 RAPID LOCK PIN ASM, LOCK GROOVE, SM

Documents

Product Drawings M.2 0.5PITCH 4.2H KEY M 30U AU

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2199230-6_B3.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2199230-6_B3.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2199230-6_B3.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

C For support call+1 800 522 6752

M.2 Connectors, Height .165 in [4.2 mm], Connector & Keying Code M, Gold, Power, -40 – 176 °F [-40 – 80 °C], M.2 NGFF



1-1773702-1_NGFF_QRG-EN

English

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance Document

English

Product Compliance Document

English