

## M12 PFT D-coded female straight 0,5m



Image is for illustration purposes only. Please refer to product description.

Part number	21 03 375 2400
Specification	M12 PFT D-coded female straight 0,5m
HARTING eCatalogue	<a href="https://b2b.harting.com/21033752400">https://b2b.harting.com/21033752400</a>

### Identification

Category	Connectors
Series	Circular connectors M12
Element	Panel feed through
Specification	With conductors for front mounting

### Version

Gender	Female
Shielding	Unshielded
Number of contacts	4
Coding	D-coding
Locking type	Screw locking
Details	Without lock nut

### Technical characteristics

Conductor cross-section	0.34 mm <sup>2</sup>
Conductor cross-section	AWG 22
Rated current	4 A
Rated voltage	250 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Overvoltage category	III



**Pushing Performance**  
 Since 1945

## Technical characteristics

Data rate	10 Mbit/s 100 Mbit/s
Insulation resistance	$>10^8 \Omega$
Contact resistance	$\leq 10 \text{ m}\Omega$
Tightening torque	2 Nm Lock nut
Limiting temperature	-30 ... +80 °C
Mating cycles	$\geq 100$
Degree of protection acc. to IEC 60529	IP67 mated condition
Isolation group	I ( $600 \leq \text{CTI}$ )
Thickness of the panel	2 ... 5 mm
Conductor length	50 cm

## Material properties

Material (insert)	Polyamide (PA)
Material (contacts)	Brass
Surface (contacts)	Au over Ni Mating side
Material (hood/housing)	Zinc die-cast
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	0d7d3693-d625-47ab-934a-d241bf72c86e
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Specifications	IEC 61076-2-101
CE	Yes



**Pushing Performance**  
Since 1945

## Commercial data

Packaging size	1
Net weight	28 g
Country of origin	Czechia
European customs tariff number	85444290
GTIN	5713140138087
eCl@ss	27440103 Sensor-actuator connector chassis (sensor technology acc.)