

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Sensor for measuring loads on the rotor blade of wind turbine generators. Robust (can be stood on). With magnetic shielding. Cable resistance compensation thanks to 6-wire connection technology.

Product description

WIL-RM-S-SG-R1 is an optimized sensor with integrated strain gauges specifically designed for use in wind turbine generators. The sensor is adhered to the inner side of the rotor blade near the base of the blade. In conjunction with a WIL-BI switchgear and controlgear assembly, loads on the rotor blade can be measured and evaluated. This allows the wind turbine generator to be controlled with load optimization, reducing the load on the rotor blades to a minimum.

The sensor is part of the Blade Intelligence rotor blade monitoring system for wind turbine generators (WTGs). The Blade Intelligence rotor blade monitoring system allows for recording and detailed analysis of typical measured values for lightning currents, temperature, ice thickness, and bending moments on the rotor of a WTG. It consists of the corresponding sensors, preassembled connecting cables, and a WIL-BI switchgear and controlgear assembly (as the evaluation unit).

Your advantages

- Robust sensor for use in the rotor blade of a WTG
- Proactive monitoring of the rotor blade
- Proven technology, optimized for the wind industry

Commercial data

Item number	1183803
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	DT02
Product key	DTHABA
GTIN	4063151222420
Weight per piece (including packing)	0.6 kg
Weight per piece (excluding packing)	0.6 kg
Customs tariff number	90303320
Country of origin	DE

Technical data

Product properties

Product type	Sensor
--------------	--------

Dimensions

External dimensions

Width / Height / Depth	48 mm / 10 mm / 130 mm
------------------------	------------------------

Cable/line

Cable entry

Connection method	M12 connector, 8-pos. (A-coded) M12 connector, 8-pos. ((A-coded))
-------------------	---

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP67
Ambient temperature (operation)	-40 °C ... 60 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Shock (operation)	30g (in accordance with EN 60068-2-27/IEC 60068-2-27)
Vibration (operation)	5g (in accordance with EN 60068-2-6/IEC 60068-2-6)
Air pressure (operation)	70 kPa ... 106 kPa (up to 3,000 m above mean sea level; at >3,000 m above mean sea level observe derating)

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



Classifications

ECLASS

ECLASS-11.0	27143137
ECLASS-12.0	27143137
ECLASS-13.0	27143137

ETIM

ETIM 8.0	EC000926
----------	----------

UNSPSC

UNSPSC 21.0	43201500
-------------	----------

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



Environmental product compliance

REACH SVHC

Lead 7439-92-1

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



Accessories

WIL-BLADE-INTELLIGENCE - Switchgear and controlgear assembly

1093550

<https://www.phoenixcontact.com/us/products/1093550>



Modular solution to monitor the rotor blades of wind turbine generators, with sensors for lightning monitoring, ice detection, and load monitoring

WIL-BI-RMS-000-00 - Switchgear and controlgear assembly

1184015

<https://www.phoenixcontact.com/us/products/1184015>



Evaluation unit for sensor data for load monitoring, including application software. Communication via Modbus/TCP and PROFINET. See "Technical data" tab for scope of supply.

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



NBC-MS-FS SCO-IE/.../... - Network cable

1408659

<https://www.phoenixcontact.com/us/products/1408659>



Network cable, Ethernet CAT5 (1 Gbps), 8-position, Variable cable type, shielded, Plug straight M12, coding: A SPEEDCON / IP67, on Socket straight M12, coding: A SPEEDCON / IP67, cable length: Free input (0.2 ... 40.0 m)

WT-BASE LS HF 6 - Cable binder base

3240708

<https://www.phoenixcontact.com/us/products/3240708>



Cable binder base, for cable binders up to 6 mm wide, self-adhesive (rubber) and screwable, 4.8 mm fixing hole, 4-sided cable binder feed-through

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



WT-HF 2,5X98 - Cable tie

3240732

<https://www.phoenixcontact.com/us/products/3240732>

Cable binders for quick and secure bundling, standard version



WMTB-AL (29X8) - Cable marker

0830805

<https://www.phoenixcontact.com/us/products/0830805>



Cable marker, Aluminum label, aluminum color, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, BLUEMARK CLED, mounting type: Assembly with cable ties, cable diameter: > 2.9 mm, lettering field size: 29 x 8 mm

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



WML HF 3(13X10)R - Wire-wrap label

0830812

<https://www.phoenixcontact.com/us/products/0830812>



Wire-wrap label, Roll, white, unlabeled, can be labeled with: THERMOMARK E. 300 (D)/600 (D), THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: adhesive, cable diameter range: 3 ... 3 mm, cable diameter: ≤ 3 mm, lettering field size: 13 x 10 mm, Number of individual labels: 5000

TSD 04 SAC - Torque screwdriver

1208429

<https://www.phoenixcontact.com/us/products/1208429>



Torque screwdriver, with preset torque of 0.4 Nm and 4 mm hexagonal drive for M12 connectors

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



SAC BIT M12-D15 - Tool

1208432

<https://www.phoenixcontact.com/us/products/1208432>



Nut for assembling sensor/actuator cables with M12 connector and M12 connectors for assembly, with a knurl diameter of 15 mm, for 4 mm hexagonal drive

TSD-M SAC-BIT ADAPTER - Adapter insert

1212600

<https://www.phoenixcontact.com/us/products/1212600>



Adapter bit for TSD-M...torque tools, E6.3-1/4" drive with 4 mm hexagon to accommodate SAC bits

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



B-STIFT - Marker pen

1051993

<https://www.phoenixcontact.com/us/products/1051993>



Marker pen, for manual labeling of unprinted Zack strips, smear-proof and waterproof, line thickness 0.5 mm

CUTFOX-S VDE - Diagonal cutter

1212207

<https://www.phoenixcontact.com/us/products/1212207>



Diagonal cutter for hard (piano wire) and soft wires, VDE 1000 V AC/1500 V DC tested

WIL-RM-S-SG-R1 - Sensor

1183803

<https://www.phoenixcontact.com/us/products/1183803>



WIREFOX 10 - Stripping tool

1212150

<https://www.phoenixcontact.com/us/products/1212150>



Stripping tool, for cables and conductors from 0.02 - 10 mm², self-adjusting, stripping length of up to 18 mm, cutting capacity of up to 10 mm² stranded/1.5 mm² solid, replaceable stripping blade

UNIFOX-CT 4,8 - Cable tie tool

1212475

<https://www.phoenixcontact.com/us/products/1212475>



Cable binder pliers, for plastic cable binders with a width of 2.2 - 4.8 mm, for a material thickness of up to 1.6 mm

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com