

N-CHANNEL ENHANCEMENT MODE VERTICAL DMOS FET

ISSUE 1 – MARCH 94


ZVN0124A

FEATURES

- * 240 Volt V_{DS}
- * $R_{DS(on)}=16\Omega$

APPLICATIONS

- * Telephone handsets



ABSOLUTE MAXIMUM RATINGS.

| PARAMETER | SYMBOL | VALUE | UNIT |
|--|---------------------|-------------|------|
| Drain-Source Voltage | V_{DS} | 240 | V |
| Continuous Drain Current at $T_{amb}=25^\circ C$ | I_D | 160 | mA |
| Pulsed Drain Current | I_{DM} | 2 | A |
| Gate Source Voltage | V_{GS} | ± 20 | V |
| Power Dissipation at $T_{amb}=25^\circ C$ | P_{tot} | 700 | mW |
| Operating and Storage Temperature Range | $T_j \cdot T_{stg}$ | -55 to +150 | °C |


ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ C$ unless otherwise stated).

| PARAMETER | SYMBOL | MIN. | MAX. | UNIT | CONDITIONS. |
|---|--------------|------|-----------|--------------------------------|--|
| Drain-Source Breakdown Voltage | BV_{DSS} | 240 | | V | $I_D=1\text{ mA}, V_{GS}=0\text{ V}$ |
| Gate-Source Threshold Voltage | $V_{GS(th)}$ | 1 | 3 | V | $ID=1\text{ mA}, V_{DS}=V_{GS}$ |
| Gate-Body Leakage | I_{GSS} | | 20 | nA | $V_{GS}=\pm 20\text{ V}, V_{DS}=0\text{ V}$ |
| Zero Gate Voltage Drain Current | I_{DSS} | | 10 100 | μA μA | $V_{DS}=240\text{ V}, V_{GS}=0$ $V_{DS}=192\text{ V}, V_{GS}=0\text{ V},$ $T=125^\circ\text{C}(2)$ |
| On-State Drain Current(1) | $I_{D(on)}$ | 500 | | mA | $V_{DS}=25\text{ V}, V_{GS}=10\text{ V}$ |
| Static Drain-Source On-State Resistance (1) | $R_{DS(on)}$ | | 16 | Ω | $V_{GS}=10\text{ V}, I_D=250\text{ mA}$ |
| Forward Transconductance (1)(2) | g_{fs} | 100 | | mS | $V_{DS}=25\text{ V}, I_D=250\text{ mA}$ |
| Input Capacitance (2) | C_{iss} | | 85 | pF | $V_{DS}=25\text{ V}, V_{GS}=0\text{ V}, f=1\text{ MHz}$ |
| Common Source Output Capacitance (2) | C_{oss} | | 20 | pF | |
| Reverse Transfer Capacitance (2) | C_{rss} | | 7 | pF | |
| Turn-On Delay Time (2)(3) | $t_{d(on)}$ | | 7 | ns | $V_{DD}\approx 25\text{ V}, I_D=250\text{ mA}$ |
| Rise Time (2)(3) | t_r | | 8 | ns | |
| Turn-Off Delay Time (2)(3) | $t_{d(off)}$ | | 16 | ns | |
| Fall Time (2)(3) | t_f | | 8 | ns | |

(1) Measured under pulsed conditions. Width=300μs. Duty cycle ≤2%

(2) Sample test.

TYPICAL CHARACTERISTICS



ZVN0124A

TYPICAL CHARACTERISTICS

