SURFBOARDS

THE BREADBOARDING MEDIUM FOR SURFACE MOUNT TAM



33000 SERIES APPLICATION SPECIFIC ADAPTERS

IDS33410

MODEL

ACCEPTS

PARTIAL LISTING

33410

INFINEON TSLP9-1

10 LEAD .5 mm PITCH DEVICES

ON SEMI UDFN10 2.5x1,0.5P

ALWAYS CONSULT DEVICE DATA SHEET TO INSURE PROPER FIT Feature Pins on .1 in. Centers designed for use with Solderless breadboards, Conventional Breadboards, and Sockets with


DEVICE LEAD WIDTH 1.0 To Max 2.6 MM

WLCSP10, 2.46x0.96

TEXAS INST.

standard .1 in. centers.

DQA (R-PSON-N10




SINGLE-IN-LINE (SIP) PINS ON .100 in. CENTÉRS

Through Hole Conversion. **JUST ADD PARTS** AND PLUG-IN TM

Use For Prototyping, Device Test or Evaluation and SMD to

FIG.	ММ	IN.	NOTE:
Α	25.4	1.0	BOARD WIDTH +5mm .020in.
В	10.16	.400	BOARD HEIGHT +5mm .020in.
С	2.54	.100	SIP PIN SPACE +20mm .008in.
D	1.65	.065	PAD CENTERLINE
E	.5	.020	DEVICE LEAD PITCH
F	1.4	.055	PAD LENGTH
G	.25	.010	PAD WIDTH
G1	.45	.018	CENTER PAD WIDTH
Н	.25	.010	GAP
- 1	2.6	.102	MAX LEAD WIDTH
J	1.0	.039	TYPICAL LEAD WIDTH
Р	3.3	.130	LENGTH FROM SHOULDER +- .5mm .020in.
S	1.57	.062	PIN SHOULDER HEGHT
W	.5	.020	PIN WIDTH

PAD SET __- G1



MOUNTING PADS ARE OVERSIZED IN LENGTH TO ACCEPT A WIDER RANGE OF DEVICE WIDTHS AND TOLERANCES AND TO PERMIT HAND SOLDERING. SEE WEBSITE FOR SOLDERING SUGGESTIONS

BOARD SPECIFICATIONS

BOARD MATERIAL: .8mm, +-.13mm .031in+-..005 in. Thick G-10 FR-4 Glass Epoxy or equivalent.

CIRCUITS: 1 oz. Copper with RoHS compliant Lead Free solder coating. Patten Position on board +- .5mm .020in.

RoHS

TOLERANCES: If not noted are +- 20%. Nominal values are given. Controlling unit is Millimeters. Values rounded to nearest decimal. Slight Variations due to manufacturing process can occur.

Copyright 2011 by Capital Advanced Technologies, Inc. All rights reserved. Surfboards is a registered trademark of Capital Advanced Technologies, Inc. The Breadboarding medium for surface mount, Just add parts and plugin, and the Leaf Circuit Logo are trademarks of Capital Advanced Technologies, Inc. All other trademarks are the property of their respective owners. Specifications, availability, and price is subject to change without notice. All information given is believed to be accurate but is not guaranteed. The user of information given or products represented by such information is responsible for determining the suitability of said information or products for a given purpose. No inducement is intended or permission granted for infringement of any patent or unauthorized use of any intellectual property of Capital Advanced Technologies or others.

CAPITAL ADVANCED TECHNOLOGIES, INC.

CAROL STREAM, ILLINOIS. USA

PHONE 630-690-1696 FAX 630-690-2498

MADE IN USA

WWW.CapitalAdvanced.Com