



About IDT

Products

Applications

Support

Document Search | Package Search | Parametric Search | Cross Reference Search | Green & RoHS | Calculators | Thermal Data | Reliability & Quality | Military

myIDT

Home > Products > Clock / Timing Devices > PC-Notebook-Server Clocks > Clock Synthesizer by Chipset Vendor > Desktop Chipsets >

Add to myIDT [?]

954141AFLFT

954141 > 954141AFLFT

Category: **Desktop Chipsets**

Generic Part: 954141 Market Group: PC CLOCK Description: PC MAIN CLOCK

ICS954141 follows Intel CK410 Yellow Cover specification. This clock synthesizer provides a single chip solution for

next generation P4 Intel processors and Intel chipsets. ICS954141 is driven with a 14.318MHz crystal.

Output Features:

- 2 0.7V current-mode differential CPU pairs
- 6 0.7V current-mode differential SRC pair
- 1 0.7V current-mode differential CPU_ITP/SRC selectable pair
- 6 PCI (33MHz)
- 3 PCICLK_F, (33MHz) free-running
- 1 USB, 48MHz
- 1 DOT, 96MHz, 0.7V current differential pair
- 1 REF, 14.318MHz

You may also like..



Parameters

| Package | SSOP 56 (PVG56) |
|-------------------------|-----------------|
| Voltage | 3.3 V |
| Package | SSOP 56 |
| Speed | NA |
| Temperature | С |
| Status | Active |
| Sample | No |
| Minimum Order Quantity | 1000 |
| Factory Order Increment | 1000 |

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

| Туре | Title | Size | Revision Date |
|--------------------------|--|-----------|------------------|
| Misc | PC Clocks Contact Info | 61 KB | 05/29/2007 |
| Product Change Notice | PCN#: TB-0510-05 New Shipping Tube for TSSOP/TVSOP/TSSOP Exposed | 202 KB | 12/13/2005 |

Package

| Description | SSOP 300 MIL, 56LD |
|----------------------------------|-----------------------------|
| Class | PLASTIC |
| Moisture Sensitivity Level (MSL) | 1 |
| Category | Green |
| Moisture Exposure Floor Life | Unlimited @ <30°C/85% RH |
| Peak Reflow Temprature | 260°C |
| Rebake Conditions | N/A |
| Length | 18.4 |
| Mark | G |
| Width | 7.5 |
| Pitch | 0.64 |
| Thickness | 2.3 |
| Status | Active |