

Contact insert - VS-09-ST-DSUB-EG - 1688793

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

D-SUB contact insert, shell size 1, with nine signal contacts, type of contact pin, with solder cup, straight, fixing with a 3 mm hole, for panel mounting frame and sleeve housing VS-09-...



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	10 pc
Weight per Piece (excluding packing)	5.51 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General data

Number of positions	9
Overvoltage category	III
Pollution degree	2

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Classifications

eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260705

Contact insert - VS-09-ST-DSUB-EG - 1688793

Classifications

eCl@ss

eCl@ss 7.0	27440309
------------	----------

ETIM

ETIM 2.0	EC000438
ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522

Approvals

Approvals

Approvals

EAC / EAC / UL Recognized


Ex Approvals

Approvals submitted

Approval details

EAC


EAC

UL Recognized 

Contact insert - VS-09-ST-DSUB-EG - 1688793

Drawings

Dimensional drawing



D-SUB contact insert